

MSDS Sheets for CUSTOM COSMETIC COLORS

This is the list of the 25 colors by Custom Cosmetic Colors.

#1, 3, 5, 7, 15, 16 18 are formulated by mixing other colors as shown below. So there will be no MSDS sheets for them.

***** THE VERY LAST TWO PAGES need to go with each color when printed.

1. Wine = Color Sheets #9 & #8
2. Mauve
3. Rose Pink = Color Sheets # 30 & #8
4. Light Pink
5. Miss Natural = Color Sheets #4 & #2
6. Coral = Color Sheet #6 & #28
7. Indian Earth = Color Sheets #19 & #27
8. Red
9. Plum
10. Orange
11. Yellow
12. Auburn
13. Dark Brown
14. Light Brown
15. Dark Ash = Color Sheets #26 & #13
16. Light Ash = Color Sheets #16, #26 & #13
17. Dark Taupe
18. Light Taupe = Color Sheets #17 & #29
19. Red Brown
20. Darkest Brown = Color Sheets #19 & 32
21. Brown Black = Color Sheets #19 & 32
22. Eyeliner Black = Color Sheet # 31 & 32
23. Gray
24. Blue
25. Green

Colors used for mixing and making colors only. Not for sell.

26. Corrective Brown
27. Tan Earth
28. Perfect Lip Color
29. Soft Taupe
30. White
31. Brown
32. Midnight black

Following are the MSDS Sheets.....

#4 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06

PRODUCT NAME: **PERMANET MAKEUP COLOR LIGHT PINK**

COMPONENTS: Isopropyl Alcohol
Deionizer Water
Glycerin
Titanium Dioxide
Yellow Iron Oxide
Red Iron Oxide
Black Iron Oxide
D&C Red 7

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: Red viscous liquid

Odor: Characteristic

Specific Gravity @ 25 Degree. Celsius.: 1.12 (H2O=1)

Solubility: Soluble in water and alcohol

Boiling Point: > 82 Degree Celsius

Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius

FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray

SPECIAL FIRE FIGHT PROCEDURE:

Use water spray to cool fire-exposed containers and structures.

Use water spray to disperse vapors; re-ignition is possible.

Use self-contained breathing apparatus and protective clothing.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS:

Vapors form from this product and may travel or be moved by air currents and ignited by pilots lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point.

Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively.

This material may produce a floating fire hazard.

#6 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06
PRODUCT NAME: PERMANENT MAKEUP COLOR CORAL
COMPONENTS: Isopropyl Alcohol Deionizer Water Glycerin CI Pigment Red 22 & 23 CI Pigment Orange 13 Titanium Dioxide Aluminum Hydroxide Amorphous Silica

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: Red viscous liquid
Odor: Characteristic
Specific Gravity @ 25 Degree. Celsius.: 0.94 (H2O=1)
Solubility: Soluble in water and alcohol
Boiling Point: > 82 Degree Celsius
Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius
FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F
EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray
SPECIAL FIRE FIGHT PROCEDURE: Use water spray to cool fire-exposed containers and structures. Use water spray to disperse vapors; re-ignition is possible. Use self-contained breathing apparatus and protective clothing.
UNUSUAL FIRE AND EXPLOSIVE HAZARDS: Vapors form from this product and may travel or be moved by air currents and ignited by pilots lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point. Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively. This material may produce a floating fire hazard.

8 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06
PRODUCT NAME: PERMANENT MAKEUP COLOR RED
COMPONENTS: Isopropyl Alcohol Deionizer Water Glycerin D&C Red 7

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: Red viscous liquid
Odor: Characteristic
Specific Gravity @ 25 Degree. Celsius.: 0.94 (H2O=1)
Solubility: Soluble in water and alcohol
Boiling Point: > 82 Degree Celsius
Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius
FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F
EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray
SPECIAL FIRE FIGHT PROCEDURE: Use water spray to cool fire-exposed containers and structures. Use water spray to disperse vapors; re-ignition is possible. Use self-contained breathing apparatus and protective clothing.
UNUSUAL FIRE AND EXPLOSIVE HAZARDS: Vapors form from this product and may travel or be moved by air currents and ignited by pilots lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point. Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively. This material may produce a floating fire hazard.

#9 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06
PRODUCT NAME: PERMANET MAKEUP COLOR PLUM COMPONENTS: Isopropyl Alcohol Deionizer Water Glycerin Titanium Dioxide Red Iron Oxide Black Iron Oxide D&C Red No.7 Ca Lake

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: Light Creamy beige viscous liquid
Odor: Characteristic
Specific Gravity @ 25 Degree. Celsius.: 1.10 (H2O=1)
Solubility: Soluble in water and alcohol
Boiling Point: > 82 Degree Celsius
Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius
FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F
EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray
SPECIAL FIRE FIGHT PROCEDURE: Use water spray to cool fire-exposed containers and structures. Use water spray to disperse vapors; re-ignition is possible. Use self-contained breathing apparatus and protective clothing.
UNUSUAL FIRE AND EXPLOSIVE HAZARDS: Vapors form from this product and may travel or be moved by air currents and ignited by pilots lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point. Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively. This material may produce a floating fire hazard.

#10 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06
PRODUCT NAME: PERMANENT MAKEUP COLOR ORANGE
COMPONENTS: Demonized Water Isopropyl Alcohol Glycerin CI Pigment Orange 13

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: Orange viscous liquid
Odor: Characteristic
Specific Gravity @ 25 Degree. Celsius.: 0.94 (H2O=1)
Solubility: Soluble in water and alcohol
Boiling Point: > 82 Degree Celsius
Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius
FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F
EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray
SPECIAL FIRE FIGHT PROCEDURE: Use water spray to cool fire-exposed containers and structures. Use water spray to disperse vapors; re-ignition is possible. Use self-contained breathing apparatus and protective clothing.
UNUSUAL FIRE AND EXPLOSIVE HAZARDS: Vapors form from this product and may travel or be moved by air currents and ignited by pilots lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point. Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively. This material may produce a floating fire hazard.

#11 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06
PRODUCT NAME: PERMANENT MAKEUP COLOR YELLOW
COMPONENTS: Isopropyl Alcohol Deionizer Water Glycerin CI Pigment Yellow 74

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: Yellow viscous liquid
Odor: Characteristic
Specific Gravity @ 25 Degree. Celsius.: 0.94 (H2O=1)
Solubility: Soluble in water and alcohol
Boiling Point: > 82 Degree Celsius
Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius
FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F
EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray
SPECIAL FIRE FIGHT PROCEDURE: Use water spray to cool fire-exposed containers and structures. Use water spray to disperse vapors; re-ignition is possible. Use self-contained breathing apparatus and protective clothing.
UNUSUAL FIRE AND EXPLOSIVE HAZARDS: Vapors form from this product and may travel or be moved by air currents and ignited by pilots lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point. Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively. This material may produce a floating fire hazard.

#12 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06
PRODUCT NAME: PERMANET MAKEUP COLOR ALBURN
COMPONENTS: Isopropyl Alcohol Deionizer Water Glycerin Yellow Iron Oxide Red Iron Oxide Black Iron Oxide Titanium Dioxide

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: Creamy Brown Pink viscous liquid
Odor: Characteristic
Specific Gravity @ 25 Degree. Celsius.: 1.15 (H2O=1)
Solubility: Soluble in water and alcohol
Boiling Point: > 82 Degree Celsius
Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius
FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F
EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray
SPECIAL FIRE FIGHT PROCEDURE: Use water spray to cool fire-exposed containers and structures. Use water spray to disperse vapors; re-ignition is possible. Use self-contained breathing apparatus and protective clothing.
UNUSUAL FIRE AND EXPLOSIVE HAZARDS: Vapors form from this product and may travel or be moved by air currents and ignited by pilots lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point. Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively. This material may produce a floating fire hazard.

13 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06

PRODUCT NAME: **PERMANET MAKEUP COLOR DARK BROWN**

COMPONENTS: Isopropyl Alcohol
Deionizer Water
Glycerin
Yellow Iron Oxide
Red Iron Oxide
Black Iron Oxide
Titanium Dioxide

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: light brown viscous liquid

Odor: Characteristic

Specific Gravity @ 25 Degree. Celsius.: 1.13 (H2O=1)

Solubility: Soluble in water and alcohol

Boiling Point: > 82 Degree Celsius

Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius

FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray

SPECIAL FIRE FIGHT PROCEDURE:

Use water spray to cool fire-exposed containers and structures.

Use water spray to disperse vapors; re-ignition is possible.

Use self-contained breathing apparatus and protective clothing.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS:

Vapors form from this product and may travel or be moved by air currents and ignited by pilots lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point.

Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively.

This material may produce a floating fire hazard.

14 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06

PRODUCT NAME: **PERMANET MAKEUP COLOR LIGHT BROWN**

COMPONENTS: Isopropyl Alcohol
Deionizer Water
Glycerin
Yellow Iron Oxide
Red Iron Oxide
Black Iron Oxide
Titanium Dioxide

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: light brown viscous liquid

Odor: Characteristic

Specific Gravity @ 25 Degree. Celsius.: 1.13 (H₂O=1)

Solubility: Soluble in water and alcohol

Boiling Point: > 82 Degree Celsius

Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius

FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray

SPECIAL FIRE FIGHT PROCEDURE:

Use water spray to cool fire-exposed containers and structures.

Use water spray to disperse vapors; re-ignition is possible.

Use self-contained breathing apparatus and protective clothing.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS:

Vapors form from this product and may travel or be moved by air currents and ignited by pilots lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point.

Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively.

This material may produce a floating fire hazard.

17 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06

PRODUCT NAME: **PERMANET MAKEUP COLOR DARK TAUPE**

COMPONENTS: Isopropyl Alcohol
Deionizer Water
Glycerin
Yellow Iron Oxide
Red Iron Oxide
Black Iron Oxide
Titanium Dioxide

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: Light Creamy Beige viscous liquid

Odor: Characteristic

Specific Gravity @ 25 Degree. Celsius.: 1.03 (H₂O=1)

Solubility: Soluble in water and alcohol

Boiling Point: > 82 Degree Celsius

Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius

FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray

SPECIAL FIRE FIGHT PROCEDURE:

Use water spray to cool fire-exposed containers and structures.

Use water spray to disperse vapors; re-ignition is possible.

Use self-contained breathing apparatus and protective clothing.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS:

Vapors form from this product and may travel or be moved by air currents and ignited by pilots lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point.

Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively.

This material may produce a floating fire hazard.

19 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06

PRODUCT NAME: **PERMANET MAKEUP COLOR RED BROWN**

COMPONENTS: Isopropyl Alcohol
Deionizer Water
Glycerin
Yellow Iron Oxide
Red Iron Oxide
Black Iron Oxide
Titanium Dioxide

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: Dark Brown viscous liquid

Odor: Characteristic

Specific Gravity @ 25 Degree. Celsius.: 1.15 (H₂O=1)

Solubility: Soluble in water and alcohol

Boiling Point: > 82 Degree Celsius

Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius

FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray

SPECIAL FIRE FIGHT PROCEDURE:

Use water spray to cool fire-exposed containers and structures.

Use water spray to disperse vapors; re-ignition is possible.

Use self-contained breathing apparatus and protective clothing.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS:

Vapors form from this product and may travel or be moved by air currents and ignited by pilots lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point.

Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively.

This material may produce a floating fire hazard.

23 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06
PRODUCT NAME: PERMANET MAKEUP COLOR GRAY
COMPONENTS: Isopropyl Alcohol Deionizer Water Glycerin Yellow Iron Oxide Red Iron Oxide Black Iron Oxide Titanium Dioxide

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: Gray viscous liquid
Odor: Characteristic
Specific Gravity @ 25 Degree. Celsius.: 1.12 (H2O=1)
Solubility: Soluble in water and alcohol
Boiling Point: > 82 Degree Celsius
Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius
FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F
EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray
SPECIAL FIRE FIGHT PROCEDURE: Use water spray to cool fire-exposed containers and structures. Use water spray to disperse vapors; re-ignition is possible. Use self-contained breathing apparatus and protective clothing.
UNUSUAL FIRE AND EXPLOSIVE HAZARDS: Vapors form from this product and may travel or be moved by air currents and ignited by pilots lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point. Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively. This material may produce a floating fire hazard.

24 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06

PRODUCT NAME: **PERMANET MAKEUP COLOR BLUE**

COMPONENTS: Isopropyl Alcohol
Deionizer Water
Glycerin
Ultramarine Blue
Titanium Dioxide

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: Light Blue viscous liquid

Odor: Characteristic

Specific Gravity @ 25 Degree. Celsius.: 1.10 (H2O=1)

Solubility: Soluble in water and alcohol

Boiling Point: > 82 Degree Celsius

Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius

FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray

SPECIAL FIRE FIGHT PROCEDURE:

Use water spray to cool fire-exposed containers and structures.

Use water spray to disperse vapors; re-ignition is possible.

Use self-contained breathing apparatus and protective clothing.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS:

Vapors form from this product and may travel or be moved by air currents and ignited by pilots lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point.

Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively.

This material may produce a floating fire hazard.

#25 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06
PRODUCT NAME: PERMANENT MAKEUP COLOR GREEN
COMPONENTS: Isopropyl Alcohol Deionizer Water Glycerin CI Pigment Green 36

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: Green viscous liquid
Odor: Characteristic
Specific Gravity @ 25 Degree. Celsius.: 0.94 (H2O=1)
Solubility: Soluble in water and alcohol
Boiling Point: > 82 Degree Celsius
Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius
FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F
EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray
SPECIAL FIRE FIGHT PROCEDURE: Use water spray to cool fire-exposed containers and structures. Use water spray to disperse vapors; re-ignition is possible. Use self-contained breathing apparatus and protective clothing.
UNUSUAL FIRE AND EXPLOSIVE HAZARDS: Vapors form from this product and may travel or be moved by air currents and ignited by pilots lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point. Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively. This material may produce a floating fire hazard.

26 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06
PRODUCT NAME: PERMANET MAKEUP COLOR CORRECTIVE BROWN
COMPONENTS: Isopropyl Alcohol Deionizer Water Titanium Dioxide Yellow Iron Oxide Red Iron Oxide Black Iron Oxide

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: light Pink viscous liquid
Odor: Characteristic
Specific Gravity @ 25 Degree. Celsius.: 1.04 (H2O=1)
Solubility: Soluble in water and alcohol
Boiling Point: > 82 Degree Celsius
Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius
FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F
EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray
SPECIAL FIRE FIGHT PROCEDURE: Use water spray to cool fire-exposed containers and structures. Use water spray to disperse vapors; re-ignition is possible. Use self-contained breathing apparatus and protective clothing.
UNUSUAL FIRE AND EXPLOSIVE HAZARDS: Vapors form from this product and may travel or be moved by air currents and ignited by pilots lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point. Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively. This material may produce a floating fire hazard.

#27 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06
PRODUCT NAME: PERMANET MAKEUP DARK BROWN COMPONENTS: Isopropyl Alcohol Deionizer Water Glycerin Yellow Iron Oxide Red Iron Oxide Black Iron Oxide Titanium Dioxide

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: Pink brown viscous liquid
Odor: Characteristic
Specific Gravity @ 25 Degree. Celsius.: 1.13 (H2O=1)
Solubility: Soluble in water and alcohol
Boiling Point: > 82 Degree Celsius
Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius
FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F
EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray
SPECIAL FIRE FIGHT PROCEDURE: Use water spray to cool fire-exposed containers and structures. Use water spray to disperse vapors; re-ignition is possible. Use self-contained breathing apparatus and protective clothing.
UNUSUAL FIRE AND EXPLOSIVE HAZARDS: Vapors form from this product and may travel or be moved by air currents and ignited by pilot's lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point. Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively. This material may produce a floating fire hazard.

#28 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06

PRODUCT NAME: **PERMANET MAKEUP PERFECT LIP COLOR**

COMPONENTS: Isopropyl Alcohol
Deionizer Water
Glycerin
D&C red No.& Ca Lake
Yellow Iron Oxide
Red Iron Oxide
Black Iron Oxide
Titanium Dioxide

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: Light brown viscous liquid

Odor: Characteristic

Specific Gravity @ 25 Degree. Celsius.: 1.15 (H2O=1)

Solubility: Soluble in water and alcohol

Boiling Point: > 82 Degree Celsius

Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius

FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray

SPECIAL FIRE FIGHT PROCEDURE:

Use water spray to cool fire-exposed containers and structures.

Use water spray to disperse vapors; re-ignition is possible.

Use self-contained breathing apparatus and protective clothing.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS:

Vapors form from this product and may travel or be moved by air currents and ignited by pilots lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point.

Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively.

This material may produce a floating fire hazard.

29 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06

PRODUCT NAME: **PERMANET MAKEUP COLOR SOFT TAUPE**

COMPONENTS: Isopropyl Alcohol
Deionizer Water
Glycerin
Yellow Iron Oxide
Red Iron Oxide
Black Iron Oxide
Titanium Dioxide

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: Light Creamy Beige viscous liquid

Odor: Characteristic

Specific Gravity @ 25 Degree. Celsius.: 1.03 (H2O=1)

Solubility: Soluble in water and alcohol

Boiling Point: > 82 Degree Celsius

Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius

FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray

SPECIAL FIRE FIGHT PROCEDURE:

Use water spray to cool fire-exposed containers and structures.

Use water spray to disperse vapors; re-ignition is possible.

Use self-contained breathing apparatus and protective clothing.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS:

Vapors form from this product and may travel or be moved by air currents and ignited by pilots lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point.

Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively.

This material may produce a floating fire hazard.

#30 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06
PRODUCT NAME: PERMANENT MAKEUPCOLOR WHITE
COMPONENTS: Isopropyl Alcohol Distilled Water Titanium Dioxide Aluminum Hydroxide Amorphous Silica

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: White viscous liquid
Odor: Characteristic
Specific Gravity @ 25 Degree. Celsius.: 0.94 (H2O=1)
Solubility: Soluble in water and alcohol
Boiling Point: > 82 Degree Celsius
Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius
FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F
EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray
SPECIAL FIRE FIGHT PROCEDURE: Use water spray to cool fire-exposed containers and structures. Use water spray to disperse vapors; re-ignition is possible. Use self-contained breathing apparatus and protective clothing.
UNUSUAL FIRE AND EXPLOSIVE HAZARDS: Vapors form from this product and may travel or be moved by air currents and ignited by pilots lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point. Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively. This material may produce a floating fire hazard.

31 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06
PRODUCT NAME: PERMANENT COLOR MIDNIGHT BLACK
COMPONENTS: Distilled Water Isopropyl Alcohol Glycerin Black Iron Oxide Silicate

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: Black viscous liquid
Odor: Characteristic
Specific Gravity @ 25 Degree. Celsius.: 0.94 (H2O=1)
Solubility: Soluble in water and alcohol
Boiling Point: > 82 Degree Celsius
Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius
FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F
EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray
SPECIAL FIRE FIGHT PROCEDURE: Use water spray to cool fire-exposed containers and structures. Use water spray to disperse vapors; re-ignition is possible. Use self-contained breathing apparatus and protective clothing.
UNUSUAL FIRE AND EXPLOSIVE HAZARDS: Vapors form from this product and may travel or be moved by air currents and ignited by pilots lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point. Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively. This material may produce a floating fire hazard.

32 MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Ship building, and Ship Breaking. This form is regarded to be in compliance with 29 CFR 1915, 1916, 1917.

SECTION I

DATE: Rev. 3/08/06

PRODUCT NAME: **PERMANENT COLOR MIDNIGHT BLACK**

COMPONENTS: Distilled Water
Isopropyl Alcohol
Glycerin
Black Iron Oxide
Silicate

SECTION II: HARZARDOUS INGREDIENTS:

Not Applicable

SECTION III: PHYSICAL DATA

Appearance @ 25 Degree Celsius.: Black viscous liquid

Odor: Characteristic

Specific Gravity @ 25 Degree. Celsius.: 0.94 (H2O=1)

Solubility: Soluble in water and alcohol

Boiling Point: > 82 Degree Celsius

Physical State: Liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 20 Degree Celsius

FLAMMABLE LIMITS IN AIR, by volume: LOWER: 2.0 UPPER: 12.7 A 200 F

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, foam or water spray

SPECIAL FIRE FIGHT PROCEDURE:

Use water spray to cool fire-exposed containers and structures.

Use water spray to disperse vapors; re-ignition is possible.

Use self-contained breathing apparatus and protective clothing.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS:

Vapors form from this product and may travel or be moved by air currents and ignited by pilots lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point.

Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively.

This material may produce a floating fire hazard.

****THE LAST TWO SHEETS HERE ARE THE SAME FOR EACH COLOR AND ARE TO BE ADDED TO EACH COLOR WHEN COPIED**

SECTION V: HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSE: SWALLOWING: Slight toxic. May cause abdominal discomfort, nausea, vomiting and diarrhea. Loss of consciousness may occur. Drowsiness may occur.
SKIN ABSORPTION: Exposure to small quantities is not expected to cause adverse health effects. Widespread or prolonged exposure may result in the absorption of harmful amounts of material, particularly in infants, leading to signs and symptoms as described for swallowing.
INHALATION: Vapor causes irritation of the respiratory tract, with coughing and chest discomfort. High concentrations of vapor may cause headache and drowsiness.
SKIN CONTACT: May cause minor irritation with itching and possible slight local redness. Prolonged or repeated contact may cause defatting and drying of the skin.
EYECONTACT: Causes irritation, experienced as stinging and discomfort or pain. Corneal injury may occur.
EMERGENCY AND FIRST AID PROCEDURES: SWALLOWING: If patient is fully conscious, give two glasses of water. Induce vomiting. Obtain medical attention.
SKIN: Remove contaminated clothing. Wash skin with soap and water. If irritation persists or if contact has been prolonged, obtain medical attention.
INHALATION: Remove to fresh air. Give artificial respiration if not breathing. If breathing is difficult, oxygen may be given by qualified personnel. Obtain medical attention.
EYES: Immediately flush eyes with water and continue washing for several minutes. Obtain medical attention.

SECTION VI: REACTIVITY DATA

STABLE	HAZARDOUS POLYMERIZATION WILL NOT OCCUR
--------	---

SECTION VII: SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Cover with absorbent material (use appropriate safety equipment), soak up and sweep into a drum. Small spills can be flushed with large amounts of water; larger spills should be collected for disposal. Extinguish and do not turn on any ignition source until the area is determined to be free from fire or explosion equipment. Avoid contact with eyes.
WASTE DISPOSAL METHOD: Incinerate in a furnace where permitted under Federal, State, and local regulations. At very low concentrations in water, this product is biodegradable in a biological wastewater treatment plant.

SECTION VIII: SPECIAL PROTECTION INFORMATION

USE PROTECTIVE GOGGLES AND SELF-CONTAINED BREATHING APPARATUS.

SECTION IX: SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING & STORING:

WARNING: Flammable

Causes eye irritation.

Keep away from heat, sparks, and flame.

Avoid contact with eyes

Keep container closed.

Use with adequate ventilation..

Wash thoroughly after handling.