

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY <i>(As Used on Label and List)</i>	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
<u>Tattoo Paint No. BD-1</u>	

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address <i>(Number, Street, City, State, and ZIP Code)</i> P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer <i>(optional)</i>

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
Phthalocyanine Blue 15:3(CAS# 147-14-8)	NA	NA	NA	10%
Acrylic Resin (TSRN00195201005-5102P)	NA	NA	NA	5%
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.50 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	1.01
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor Blue acrylic dispersion with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA NA			
Unusual Fire and Explosion Hazards NA NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (<i>Materials to Avoid</i>) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or resin. Chronic: Unknown.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>)		
None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (<i>As Used on Label and List</i>)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
<u>Tattoo Paint No. BLK</u>	

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (<i>Number, Street, City, State, and ZIP Code</i>) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (<i>optional</i>)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(<i>optional</i>)
Carbon Black 7 (CAS# 1333-86-41)	NA	NA	NA	10%
Acrylic Resin (TSRN00195201005-5102P) (Proprietary resin)	NA	NA	NA	5%
Isopropyl Alcohol (CAS# 67-63-0) (pH = 8.65 neat)	400ppm	NA	NA	10%
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	1.07
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor Black acrylic dispersion with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA			
Unusual Fire and Explosion Hazards NA			
NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (<i>Materials to Avoid</i>) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or resin. Chronic: Unknown.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

WAIVER OF LIABILITY

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (<i>As Used on Label and List</i>)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
<u>Tattoo Paint No. BRN</u>	

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (<i>Number, Street, City, State, and ZIP Code</i>) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (<i>optional</i>)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(<i>optional</i>)
Mixture of Carbazole Violet 23 (CAS# 6358-30-1) and Pigment Orange 16 (CAS# 6505-28-8)	NA	NA	NA	10%
Acrylic Resin (TSRN00195201005-5102P)	NA	NA	NA	5%
(Proprietary resin)				
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.50 neat)				
NA				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	1.01
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor Brown acrylic dispersion with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA			
NA			
Unusual Fire and Explosion Hazards NA			
NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (<i>Materials to Avoid</i>) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or resin. Chronic: Unknown.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

WAIVER OF LIABILITY

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List) <u>Tattoo Paint No. BRO</u>	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
---	--

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (Number, Street, City, State, and ZIP Code) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (optional)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
Pigment Yellow 74(CAS#635b-91-32)	NA	NA	NA	10%
Pigment Orange 16(CAS#6505-28-8)	NA	NA	NA	1%
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.46 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	1.04
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor Orange and yellow pigment blend with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA NA			
Unusual Fire and Explosion Hazards NA NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (Materials to Avoid) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or dispersion agent. Chronic: None known for dispersion agent. Pigment is skin irritant for some individuals.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

WAIVER OF LIABILITY

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (<i>As Used on Label and List</i>)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
<u>Tattoo Paint No. BUB</u>	

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (<i>Number, Street, City, State, and ZIP Code</i>) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (<i>optional</i>)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(<i>optional</i>)
Titanium Dioxide (CAS# 13463-67-7)	NA	NA	NA	10%
Pigment Red 210(CAS#2787-76-7)	NA	NA	NA	.5%
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.46 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	1.30
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor White and red pigment blend dispersion with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA			
NA			
Unusual Fire and Explosion Hazards NA			
NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (<i>Materials to Avoid</i>) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or dispersion agent. Chronic: None known for dispersion agent. Pigment is skin irritant for some individuals.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

WAIVER OF LIABILITY

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (<i>As Used on Label and List</i>)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
<u>Tattoo Paint No. ELB</u>	

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (<i>Number, Street, City, State, and ZIP Code</i>) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (<i>optional</i>)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(<i>optional</i>)
Titanium Dioxide (CAS# 13463-67-7)	NA	NA	NA	10%
Pigment Blue 15.3(CAS#147-14-8)	NA	NA	NA	5%
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.46 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	1.30
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor White and blue pigment blend with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA NA			
Unusual Fire and Explosion Hazards NA NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (Materials to Avoid) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or dispersion agent. Chronic: None known for dispersion agent. Pigment is skin irritant for some individuals.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

WAIVER OF LIABILITY

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (<i>As Used on Label and List</i>)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
<u>Tattoo Paint No. GD-1</u>	

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (<i>Number, Street, City, State, and ZIP Code</i>) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (<i>optional</i>)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(<i>optional</i>)
Pigment Green 7 (CAS# 1328-53-6)	NA	NA	NA	10%
Acrylic Resin (TSRN00195201005-5102P)	NA	NA	NA	5%
(Proprietary resin)				
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.58 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	1.14
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor Green acrylic dispersion with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA			
NA			
Unusual Fire and Explosion Hazards NA			
NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (<i>Materials to Avoid</i>) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or resin. Chronic: Unknown.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>)		
None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

WAIVER OF LIABILITY

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (<i>As Used on Label and List</i>)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
<u>Tattoo Paint No. HTP</u>	

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (<i>Number, Street, City, State, and ZIP Code</i>) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (<i>optional</i>)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(<i>optional</i>)
Titanium Dioxide (CAS# 13463-67-7)	NA	NA	NA	8%
Pigment Red 210(CAS#2787-76-7)	NA	NA	NA	2%
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.46 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	1.25
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor White and red pigment blend dispersion with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA			
NA			
Unusual Fire and Explosion Hazards NA			
NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (Materials to Avoid) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or dispersion agent. Chronic: None known for dispersion agent. Pigment is skin irritant for some individuals.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

WAIVER OF LIABILITY

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (As Used on Label and List) <u>Tattoo Paint No. LAV</u>	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
--	---

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (Number, Street, City, State, and ZIP Code) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (optional)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
Titanium Dioxide (CAS# 13463-67-7)	NA	NA	NA	10%
Carbazole Violet 23(CAS#6358-30-1)	NA	NA	NA	.5%
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.46 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	1.30
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor White and violet pigment blend with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA NA			
Unusual Fire and Explosion Hazards NA NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (<i>Materials to Avoid</i>) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or dispersion agent. Chronic: None known for dispersion agent. Pigment is skin irritant for some individuals.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

WAIVER OF LIABILITY

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (<i>As Used on Label and List</i>)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
<u>Tattoo Paint No. LBR</u>	

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (<i>Number, Street, City, State, and ZIP Code</i>) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (<i>optional</i>)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(<i>optional</i>)
Pigment Violet 23(CAS#6358-30-1)	NA	NA	NA	.25%
Pigment Orange 16(CAS#6505-28-8)	NA	NA	NA	10%
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.46 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	1.02
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor Orange and violet pigment blend with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA			
NA			
Unusual Fire and Explosion Hazards NA			
NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (<i>Materials to Avoid</i>) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or dispersion agent. Chronic: None known for dispersion agent. Pigment is skin irritant for some individuals.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

WAIVER OF LIABILITY

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (As Used on Label and List) <u>Tattoo Paint No. LFG</u>	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
--	---

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (Number, Street, City, State, and ZIP Code) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (optional)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
Pigment Yellow 74(CAS#635b-91-32)	NA	NA	NA	10%
Pigment Green 7(CAS#1328-53-6)	NA	NA	NA	3%
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.46 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	1.05
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor Green and yellow Pigment blend with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA NA			
Unusual Fire and Explosion Hazards NA NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (Materials to Avoid) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or dispersion agent. Chronic: None known for dispersion agent. Pigment is skin irritant for some individuals.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

WAIVER OF LIABILITY

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (As Used on Label and List) <u>Tattoo Paint No. LYM</u>	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
--	---

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (Number, Street, City, State, and ZIP Code) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (optional)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
Pigment Yellow 74(CAS#635b-91-32)	NA	NA	NA	10%
Pigment Green 7(CAS#1328-53-6)	NA	NA	NA	.25%
Titanium Dioxide (CAS# 13463-67-7)	NA	NA	NA	2%
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.46 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	1.17
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor Green, yellow, and white pigment blend with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA			
NA			
Unusual Fire and Explosion Hazards NA			
NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (<i>Materials to Avoid</i>) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or dispersion agent. Chronic: None known for dispersion agent. Pigment is skin irritant for some individuals.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

WAIVER OF LIABILITY

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (As Used on Label and List) <u>Tattoo Paint No. MD-1</u>	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
---	---

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (Number, Street, City, State, and ZIP Code) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (optional)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
Pigment Red 122 (CAS# 980-26-7)	NA	NA	NA	10%
Acrylic Resin (TSRN00195201005-5102P)	NA	NA	NA	5%
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.55 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	91	Specific Gravity (H ₂ O = 1)	0.90
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor Red acrylic dispersion with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA NA			
Unusual Fire and Explosion Hazards NA NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (<i>Materials to Avoid</i>) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or resin. Chronic: Unknown.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>)		
None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (<i>As Used on Label and List</i>)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
<u>Tattoo Paint No. OD-5</u>	

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (<i>Number, Street, City, State, and ZIP Code</i>) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (<i>optional</i>)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(<i>optional</i>)
Pigment Orange 16 (CAS# 6505-28-8)	NA	NA	NA	10%
Acrylic Resin (TSRN00195201005-5102P)	NA	NA	NA	5%
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.53 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	0.960
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor Orange acrylic dispersion with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA NA			
Unusual Fire and Explosion Hazards NA NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (<i>Materials to Avoid</i>) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or resin. Chronic: Unknown.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (<i>As Used on Label and List</i>)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
<u>Tattoo Paint No. RD-1</u>	

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (<i>Number, Street, City, State, and ZIP Code</i>) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (<i>optional</i>)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(<i>optional</i>)
Pigment Red 210 (CAS# 2787-76-7)	NA	NA	NA	10%
Acrylic Resin (TSRN00195201005-5102P)	NA	NA	NA	5%
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.50 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	91	Specific Gravity (H ₂ O = 1)	0.993
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor Red acrylic dispersion with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA NA			
Unusual Fire and Explosion Hazards NA NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (<i>Materials to Avoid</i>) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or resin. Chronic: Unknown.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (<i>As Used on Label and List</i>)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
<u>Tattoo Paint No. RD-2</u>	

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (<i>Number, Street, City, State, and ZIP Code</i>) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (<i>optional</i>)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(<i>optional</i>)
Pigment Red 22 (CAS# 6448-95-9)	NA	NA	NA	10%
Acrylic Resin (TSRN00195201005-5102P) (Proprietary resin)	NA	NA	NA	5%
Isopropyl Alcohol (CAS# 67-63-0) (pH = 8.56 neat)	400ppm	NA	NA	10%
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	91	Specific Gravity (H ₂ O = 1)	1.043
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor Red ² acrylic dispersion with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA			
NA			
Unusual Fire and Explosion Hazards NA			
NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (<i>Materials to Avoid</i>) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or resin. Chronic: Unknown.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

WAIVER OF LIABILITY

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (<i>As Used on Label and List</i>)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
<u>Tattoo Paint No. RD-4</u>	

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (<i>Number, Street, City, State, and ZIP Code</i>) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (<i>optional</i>)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(<i>optional</i>)
Napthol Red (CAS# 36968-27-1)	NA	NA	NA	10%
Acrylic Resin (TSRN00195201005-5102P)	NA	NA	NA	5%
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.50 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	91	Specific Gravity (H ₂ O = 1)	0.94
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor Red acrylic dispersion with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA			
NA			
Unusual Fire and Explosion Hazards NA			
NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (<i>Materials to Avoid</i>) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or resin. Chronic: Unknown.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (<i>As Used on Label and List</i>) <u>Tattoo Paint No. RD-6</u>	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
---	--

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (<i>Number, Street, City, State, and ZIP Code</i>) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (<i>optional</i>)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (<i>optional</i>)
Pigment Red 269 (CAS#67990-05-0)	NA	NA	NA	10%
Isopropyl Alcohol (CAS# 67-63-0) (pH = 8.46 neat)	400ppm	NA	NA	10%
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	93
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor red pigment dispersion with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA			
NA			
Unusual Fire and Explosion Hazards NA			
NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (Materials to Avoid) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or dispersion agent. Chronic: None known for dispersion agent. Pigment is skin irritant for some individuals.			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>)		
None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None

Protective Gloves None required	Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.	
Work/Hygienic Practices Normal care and cleanliness.	
Page 4 *U.S.G.P.O. 1986-491 – 529/45775	

WAIVER OF LIABILITY

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (As Used on Label and List) <u>Tattoo Paint No. SKB</u>	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
---	--

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (Number, Street, City, State, and ZIP Code) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (optional)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
Titanium Dioxide (CAS# 13463-67-7)	NA	NA	NA	9.25%
Pigment Blue 15.3(CAS#147-14-8)	NA	NA	NA	.75%
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.46 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	1.35
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor White and blue pigment blend with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA NA			
Unusual Fire and Explosion Hazards NA NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (Materials to Avoid) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or dispersion agent. Chronic: None known for dispersion agent. Pigment is skin irritant for some individuals.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

WAIVER OF LIABILITY

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (<i>As Used on Label and List</i>)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
<u><i>Tattoo Paint No. TEA</i></u>	

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (<i>Number, Street, City, State, and ZIP Code</i>) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (<i>optional</i>)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(<i>optional</i>)
Titanium Dioxide (CAS# 13463-67-7)	NA	NA	NA	9%
Pigment Green 7 (CAS#1328-53-6)	NA	NA	NA	1%
Pigment Blue 15.3 (CAS#147-14-8)	NA	NA	NA	1%
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.46 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	1.20
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor White, green and blue pigment blend dispersion with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA			
NA			
Unusual Fire and Explosion Hazards NA			
NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (<i>Materials to Avoid</i>) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or dispersion agent. Chronic: None known for dispersion agent. Pigment is skin irritant for some individuals.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

WAIVER OF LIABILITY

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (<i>As Used on Label and List</i>)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
<u>Tattoo Paint No. TRP</u>	

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (<i>Number, Street, City, State, and ZIP Code</i>) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (<i>optional</i>)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(<i>optional</i>)
Titanium Dioxide (CAS# 13463-67-7)	NA	NA	NA	10%
Carbazole Violet 23(CAS#6358-30-1)	NA	NA	NA	2%
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.46 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	1.20
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor White and violet pigment blend with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA			
NA			
Unusual Fire and Explosion Hazards NA			
NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (Materials to Avoid) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or dispersion agent. Chronic: None known for dispersion agent. Pigment is skin irritant for some individuals.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

WAIVER OF LIABILITY

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (<i>As Used on Label and List</i>)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
<u>Tattoo Paint No. TRO</u>	

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (<i>Number, Street, City, State, and ZIP Code</i>) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (<i>optional</i>)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(<i>optional</i>)
Titanium Dioxide (CAS# 13463-67-7)	NA	NA	NA	10%
Pigment Green 7 (CAS#1328-53-6)	NA	NA	NA	2%
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.46 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	1.20
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor White and green pigment blend with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA NA			
Unusual Fire and Explosion Hazards NA NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (Materials to Avoid) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or dispersion agent. Chronic: None known for dispersion agent. Pigment is skin irritant for some individuals.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

WAIVER OF LIABILITY

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (<i>As Used on Label and List</i>)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
<u>Tattoo Paint No. VD-1</u>	

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (<i>Number, Street, City, State, and ZIP Code</i>) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (<i>optional</i>)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(<i>optional</i>)
Carbazole Violet 23(CAS# 6358-30-1)	NA	NA	NA	10%
Acrylic Resin (TSRN00195201005-5102P)	NA	NA	NA	5%
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.56 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	91	Specific Gravity (H ₂ O = 1)	1.05
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor Violet acrylic dispersion with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA			
NA			
Unusual Fire and Explosion Hazards NA			
NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (<i>Materials to Avoid</i>) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or resin. Chronic: Unknown.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>)		
None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (As Used on Label and List) <u>Tattoo Paint No. WD-1</u>	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
--	--

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (Number, Street, City, State, and ZIP Code) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (optional)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
Titanium Dioxide (CAS# 13463-67-7)	NA	NA	NA	10%
Isopropyl Alcohol (CAS# 67-63-0) (pH = 8.46 neat)	400ppm	NA	NA	10%
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	1.40
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor White pigment dispersion with faint odor.			
Section IV – Fire and Explosion Hazard Data			
Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA			
NA			
Unusual Fire and Explosion Hazards NA			
NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (<i>Materials to Avoid</i>) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
-------------------	-----------------	-----------	----------------

Health Hazards (Acute and Chronic)

Acute: None known for the pigment or dispersion agent.
Chronic: None known for dispersion agent. Pigment is skin irritant for some individuals.

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>)		
None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None

Protective Gloves None required	Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.	
Work/Hygienic Practices Normal care and cleanliness.	
Page 4 *U.S.G.P.O. 1986-491 – 529/45775	

WAIVER OF LIABILITY

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (<i>As Used on Label and List</i>)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
<u>Tattoo Paint No. YD-2</u>	

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (<i>Number, Street, City, State, and ZIP Code</i>) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (<i>optional</i>)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(<i>optional</i>)
C.I. Pigment Yellow 3(CAS# 648668-23-3)	NA	NA	NA	10%
Acrylic Resin (TSRN00195201005-5102P)	NA	NA	NA	5%
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.60 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	1.13
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor Yellow acrylic dispersion with faint odor.			

Section IV – Fire and explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA NA			
Unusual Fire and Explosion Hazards NA NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (Materials to Avoid) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or resin. Chronic: Unknown.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (<i>As Used on Label and List</i>)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
<u>Tattoo Paint No. YD-4</u>	

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (<i>Number, Street, City, State, and ZIP Code</i>) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (<i>optional</i>)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(<i>optional</i>)
Pigment Yellow 74 (CAS# 635B-91-32)	NA	NA	NA	10%
Acrylic Resin (TSRN00195201005-5102P) (Proprietary resin)	NA	NA	NA	5%
Isopropyl Alcohol (CAS# 67-63-0) (pH = 8.43 neat)	400ppm	NA	NA	10%
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	92	Specific Gravity (H ₂ O = 1)	1.07
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor Yellow pigment dispersion with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA			
NA			
Unusual Fire and Explosion Hazards NA			
NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (<i>Materials to Avoid</i>) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or dispersion agent. Chronic: None known for the pigment or dispersion agent.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

WAIVER OF LIABILITY

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 Consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (<i>As Used on Label and List</i>) <u>Tattoo Paint No. YD-7</u>	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
--	---

Section I

Manufacturer's Name Dynamic Color Co.	Emergency Telephone Number (954) 462-0261
Address (<i>Number, Street, City, State, and ZIP Code</i>) P.O. Box 21083 Ft. Lauderdale	Telephone Number for Information (954) 462-0261
Florida	Date Prepared 4-12-01
33335	Signature of Preparer (<i>optional</i>)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(<i>optional</i>)
Pigment Yellow 83 (CAS# 5567-15-7)	NA	NA	NA	10%
Proprietary Dispersing Agent	NA	NA	NA	5%
Isopropyl Alcohol (CAS# 67-63-0)	400ppm	NA	NA	10%
(pH = 8.59 neat)				
NA				
NA				
NA				
NA				
NA				
Page 1				

Section III – Physical/Chemical Characteristics

Boiling Point (deg.C.)	91	Specific Gravity (H ₂ O = 1)	1.02
Vapor Pressure (mm Hg.)	50	Melting Point (deg.C.)	Ca. 0
Vapor Density (AIR = 1)	Ca. 2	Evaporation Rate (Butyl Acetate = 1)	< 1
Solubility in Water Dispersible in all proportions.			
Appearance and Odor Yellow pigment dispersion with faint odor.			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) None, TOC	Flammable Limits NA	NA	UEL NA
Extinguishing Media NA			
Special Fire Fighting Procedures NA NA			
Unusual Fire and Explosion Hazards NA NA			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid NA
Stability	Stable	X	Oxidizing agents NA
Incompatibility (<i>Materials to Avoid</i>) NA			
Hazardous Decomposition or Byproducts NA			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NA

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Acute: None known for the pigment or dispersion agent. Chronic: None known for the pigment or dispersion agent.			
Page 2			

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? NA
Signs and Symptoms of Exposure			
None			
Medical Conditions Generally Aggravated by Exposure			
None known.			
Emergency and First Aid Procedures			
<p>For skin exposure, no irritation is likely. For eye exposure, flush with large quantities of water. For inhalation, no irritation is likely. For ingestion, drink two glasses of water, induce vomiting and seek medical help.</p>			
Section VII– Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
Absorb liquid with paper towels or other absorbent material.			
Waste Disposal Method			
Dispose of material in accordance with local, state and federal regulations			
Steps to Be Taken in Handling and Storing			
<p>Special gloves and clothing not generally required but safety glasses should be used. For prolonged exposure, use neoprene or rubber gloves. Store in cool well-ventilated area.</p>			
Other Precautions			
If large quantities are involved, use safety shower and eyewash fountain.			
Page 3			

Section VIII– Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with normal handling.		
Ventilation None required.	Local Exhaust None required.	Special None
	Mechanical (<i>General</i>) None required.	Other None
Protective Gloves None required		Eye Protection Yes
Other Protective Clothing or Equipment (<i>Specify Type</i>) Generally not required.		
Work/Hygienic Practices Normal care and cleanliness.		
Page 4 *U.S.G.P.O. 1986-491 – 529/45775		

WAIVER OF LIABILITY

THE MSDS INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALL DATA ARE PROVIDED WITHOUT WARRANTY, EXPRESS OR IMPLIED, REGARDING THEIR CORRECTNESS OR ACCURACY.

APPLIED CONSUMER SERVICES, INC. AND DYNAMIC COLOR CO., SHALL NOT BE LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING, STORAGE, OR CONTACT WITH THE ABOVE PRODUCT. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR THE USE AND HANDLING OF THE PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE RESULTING FROM THE USE OF THE PRODUCT.