

2,2622 Lambert St. #306 Lake Forest, CA 92630 949.916.1054

How to Use Your New Bishop

- This Bishop has the all new SWISS MAXON MOTOR and will run one volt lower than the older Mabuchi Motors in our previous machines.
- For color packing and shading, run the machine between 7.5 and 8.5 volts depending on your hand speed and style.
- For lining, run the machine between 8 and 9 volts depending on your hand speed and stlye.
- Other rotary companies offer adjustable gove, but we don't believe this is best for rotaries. We have a spring that offers just the right amount of give and at that point, you use your hand speed and hand pressure to adjust your give. This way, it's more natural and a better way to learn rotaries. I have called this term "Organic Give".
- For proper Lube, only use the *SuperLube* packs provided in your order. You use the Super Lube every 6 weeks or every 100 hours. You will need to put 1 drop of lube on all 4 sides of the black slide and run it for 30 seconds to a minute and it will absorb the lube while it's running. Be careful to not over lube the black slide.

CAUTION: DO NOT USE ANY OIL TO LUBE YOUR MACHINE AS IT WILL DAMAGE THE MOTOR. ALSO, DO NOT SPRAY YOUR MACHINE DOWN WITH MADACIDE, GREEN SOAP OR ANY LIQUIDS AS THEY WILL SEEP INTO THE MOTOR HOUSING THE WARRANTY.