

MATERIAL SAFETY DATA SHEET

Prepared to U.S. OSHA, CMA, ANSI, Canadian WHMIS, European Union Standards, Australian WorkSafe, the Japanese Industrial Standard JIS Z 7250: 2000 and the Global Harmonization Standard

PART I What is the material and what do I need to know in an emergency?

1. IDENTIFICATION of the SUBSTANCE or PREPARATION

IDENTIFICATION OF SUBSTANCE/PREPARATION:

TRADE NAME (AS LABELED):

CHEMICAL NAME/CLASS:

SYNONYMS:

PRODUCT USE:

U.N. NUMBER:

U.N. DANGEROUS GOODS CLASS/SUBSIDIARY RISK:

HAZCHEM CODE (AUSTRALIA):

POISONS SCHEDULE NUMBER (AUSTRALIA):

COMPANY/UNDERTAKING IDENTIFICATION:

U.S. SUPPLIER/MANUFACTURER'S NAME:

ADDRESS:

INFORMATION PHONE:

EMERGENCY PHONE:

EMAIL:

DATE OF PREPARATION:

DATE OF REVISION:

Silverback Ink Original Grey Wash Series (X1, X2, X3, X4)

Water-Based Ink

Not Applicable

Various Uses

None Allocated

None Allocated

None Allocated

None Allocated

SILVERBACK INK CORP

4869 Fountain Ave

Los Angeles, CA 90029, USA

1-323-669-8282

CHEMTREC: (800) 424-9300 (U.S, Canada, Puerto Rico) 24 hours

CHEMTREC: +1-703-527-3887 [collect] (International) 24 hours

tattoodyou@aol.com

May 17, 2007

October 19, 2010

NOTE: ALL United States Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalent Standards, Canadian WHMIS [Controlled Products Regulations], all applicable EU Directives through EC 1907: 2006, the European Union CLP EC 1272/2008 and the Global Harmonization Standard, Australian [NOHSC:2011 (2003)], and Japanese Industrial Standard (JIS Z 7250: 2000) required information is included in appropriate sections based on the U.S. ANSI Z400.1-2004 format. These products have been classified in accordance with the hazard criteria of the countries listed above.

2. HAZARD IDENTIFICATION

GLOBAL HARMONIZATION AND EU CLP REGULATION (EC) 1272/2008 LABELING AND CLASSIFICATION: Classified in accordance with CLP Regulation (EC) 1272/2008. For additional information on classification under (67/548/EEC), see below.

Classification: Not Applicable

Signal Word: Not Applicable

Hazard Statement Codes: Not Applicable

Prevention Precautionary Statements: Not Applicable

Response Precautionary Statements: Not Applicable

Storage Precautionary Statements: Not Applicable

Disposal Precautionary Statements: Not Applicable

Hazard Symbol: Not Applicable

See Section 15 for full text of Hazard and Precautionary Statements

EU LABELING AND CLASSIFICATION 67/548/EEC: Classified in accordance with the European Community Council Directive 67/548/EEC or subsequent Directives.

EU CLASSIFICATION: Not Applicable

EU RISK PHRASES: Not Applicable

EU SAFETY PHRASES: Not Applicable

See Section 15 for full text of Ingredient Risk and Safety Phrases

AUSTRALIAN NATIONAL OCCUPATION HEALTH and SAFETY COMMISSION LABELING/CLASSIFICATION: Classified in accordance with the Australian National Occupational Health and Safety Commission [NOHSC(1008:2004)].

CLASSIFICATION: Not Applicable

RISK PHRASES: Not Applicable

SAFETY PHRASES: Not Applicable



See Section 15 for details on classification

EMERGENCY OVERVIEW: Product Description: These products are grey liquids with a mild odor. **Health Hazards:** The primary health hazard associated with this material is the potential for mild irritation of contaminated tissue. The ink may stain skin, eyes, other contaminated tissue, and objects. **Flammability Hazards:** These products are not flammable. **Reactivity Hazards:** This material is not reactive. **Environmental Hazards:** These products may have adverse effects when released into the environment. **Emergency Recommendations:** Emergency responders must wear the personal protective equipment suitable for the situation to which they are responding.

3. COMPOSITION and INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS #	EINECS #	Japanese ENCS #	Australian AICS	% w/v	EU Hazard Symbol (67/548/EEC)	GHS/EU Hazard Symbol (1272/2008 EC)	EU Classification (67/548/EEC) GHS & EU Classification (1272/2008 EC) Risk Phrases/Hazard Statements
---------------	-------	----------	-----------------	-----------------	-------	-------------------------------	-------------------------------------	--



SILVERBACK INK ORIGINAL GREY WASH X1 & SILVERBACK INK ORIGINAL GREY WASH X2

Proprietary Organic Extract		Unlisted	Unlisted	Listed	30-40	Not Applicable	Not Applicable	EU 67/548 Hazard Classification: Not Applicable. GHS & EU 1272/2008 Classification: Not Applicable.
Proprietary Black Pigment			Excepted as a Mineral	Listed	3-7			SELF CLASSIFICATION (Inhalation of particulates) EU 67/548 Hazard Classification: Carcinogenic Cat. 3 EU 67/548 Risk Phrases: R: 40 GHS & EU 1272/2008 Classification: Carcinogenic Category 2 GHS & EU 1272/2008 Hazard Statement Code: H351
Water and other components. Each of the other components is present in less than 1 percent concentration (0.1% concentration for potential carcinogens, reproductive toxins, respiratory tract sensitizers, and mutagens).					Balance	Not Applicable	Not Applicable	EU 67/548 Hazard Classification: Not Applicable. GHS & EU 1272/2008 Classification: Not Applicable.

See Section 15 for full EU classification information of product and components.

SILVERBACK INK ORIGINAL GREY WASH SERIES [X1, X2, X3, X4] MSDS

3. COMPOSITION and INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS #	EINECS #	Japanese ENCS #	Australian AICS	% w/v	EU Hazard Symbol (67/548/EEC)	GHS/EU Hazard Symbol (1272/2008 EC)	EU Classification (67/548/EEC) GHS & EU Classification (1272/2008 EC) Risk Phrases/Hazard Statements
SILVERBACK INK ORIGINAL GREY WASH X3 & SILVERBACK INK ORIGINAL GREY WASH X4								
Proprietary Organic Extract		Unlisted	Unlisted	Listed	30–40	Not Applicable	Not Applicable	EU 67/548 Hazard Classification: Not Applicable. GHS & EU 1272/2008 Classification: Not Applicable.
Proprietary Black Pigment			Excepted as a Mineral	Listed	7–13			SELF CLASSIFICATION (Inhalation of particulates) EU 67/548 Hazard Classification: Carcinogenic Cat. 3 EU 67/548 Risk Phrases: R: 40 GHS & EU 1272/2008 Classification: Carcinogenic Category 2 GHS & EU 1272/2008 Hazard Statement Code: H351
Water and other components. Each of the other components is present in less than 1 percent concentration (0.1% concentration for potential carcinogens, reproductive toxins, respiratory tract sensitizers, and mutagens).					Balance	Not Applicable	Not Applicable	EU 67/548 Hazard Classification: Not Applicable. GHS & EU 1272/2008 Classification: Not Applicable.

See Section 15 for full EU classification information of product and components.

PART II What should I do if a hazardous situation occurs?

4. FIRST-AID MEASURES

Contaminated individuals must be taken for medical attention if any adverse effect occurs. Rescuers should be taken for medical attention if necessary. Take a copy of the label and MSDS to health professional with victim.

SKIN EXPOSURE: If this material contaminates the skin, immediately begin decontamination with running water and soap. The minimum recommended flushing time is 20 minutes. Remove exposed or contaminated clothing, taking care not to contaminate eyes. The contaminated individual must seek medical attention if any adverse effect occurs.

EYE EXPOSURE: If vapors, sprays, or mists of this material enter the eyes, open the contaminated individual's eyes while under gently running water. Use sufficient force to open eyelids. Have the contaminated individual "roll" eyes. Minimum flushing is for 20 minutes. The contaminated individual must seek medical attention if any adverse effect occurs.

INHALATION: If vapors, sprays, or mists of this material are inhaled, remove the contaminated individual to fresh air. If necessary, remove or cover gross contamination to avoid exposure to rescuers. Seek medical attention if adverse effect occurs.

INGESTION: If this material is swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. DO NOT INDUCE VOMITING, unless directed by medical personnel. Have victim rinse mouth with water if conscious. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or unable to swallow. If vomiting occurs, lean patient forward or place on left side (head-down position if possible) to maintain an open airway and prevent aspiration.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing dermatitis and other skin conditions may be aggravated by prolonged overexposures to this material.

RECOMMENDATIONS TO PHYSICIANS: Treat symptoms and eliminate overexposure.

5. FIRE-FIGHTING MEASURES

FLASH POINT: Not flammable.

AUTOIGNITION TEMPERATURE: Not applicable.

FLAMMABLE LIMITS (in air by volume, %): Not applicable.

FIRE EXTINGUISHING MATERIALS: Unless incompatibilities exist for surrounding materials, carbon dioxide, water spray, 'ABC' type chemical extinguishers, foam, dry chemical and halon extinguishers can be used to fight fires involving these products.

FIRE EXTINGUISHERS TO USE NOT BE USED: None known.


UNUSUAL FIRE AND EXPLOSION HAZARDS: When involved in a fire, this material may decompose and produce irritating vapors and toxic gases (e.g., carbon oxides).

Explosion Sensitivity to Mechanical Impact: Not sensitive.

Explosion Sensitivity to Static Discharge: Not sensitive.

SPECIAL FIRE-FIGHTING PROCEDURES: Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Due to the presence of colorants, the runoff water from these products can discolor contaminated objects. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas. If necessary, rinse fire-response equipment with soapy water before returning it to service.

NFPA RATING



Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate
3 = Serious 4 = Severe

6. ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK RESPONSE: Proper protective equipment should be used. In the event of a spill, clear the area and protect people. The atmosphere must have levels of components lower than those listed in Section 8, (Exposure Controls and Personal Protective Equipment) if applicable, and have at least 19.5 percent oxygen before personnel can be allowed into the area without Self-Contained Breathing Apparatus (SCBA).

6. ACCIDENTAL RELEASE MEASURES (Continued)

SPILL AND LEAK RESPONSE (continued):

Small Spills: For incidental spills (e.g., less than 1 liters of liquid from a bottle), wear rubber gloves, splash goggles, and appropriate body protection. Wipe up spilled liquid with polypads or other suitable absorbent materials. Wash contaminated area with soap and water, absorb with paper towels, and rinse with water.

Large Spills: For spill of 10 liters or more, trained personnel following pre-planned procedures should handle non-incidental releases. Minimum Personal Protective Equipment should be rubber gloves, rubber boots, face shield, and Tyvek suit. Minimum level of personal protective equipment for releases in which the level of oxygen is less than 19.5% or is unknown must be **Level B: triple-gloves (rubber gloves and nitrile gloves over latex gloves), chemical resistant suit and boots, hard hat, and Self-Contained Breathing Apparatus**. Wipe up spilled liquid with polypads or other suitable absorbent materials. Prevent material from entering sewer or confined spaces, waterways, soil or public waters. Monitor area and confirm levels are below exposure limits given in Section 8 (Exposure Controls-Personal Protection), if applicable, before non-response personnel are allowed into the spill area. Absorb spilled liquid with polypads or other suitable absorbent materials. Rinse area thoroughly with soapy water after liquid has dried. Decontaminate the area thoroughly. If necessary, discard all stained response equipment or rinse with soapy water before returning such equipment to service.

Place all spill residue in an appropriate container and seal. Decontaminate the area thoroughly. If necessary, discard all stained response equipment or rinse with soapy water before returning such equipment to service. Do not mix with wastes from other materials. Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13, Disposal Considerations). For spills on water, contain, minimize dispersion and collect. Dispose of recovered material and report spill per regulatory requirements.

PART III *How can I prevent hazardous situations from occurring?*

7. HANDLING and STORAGE

WORK AND HYGIENE PRACTICES: As with all chemicals, avoid getting this material ON YOU or IN YOU. Wash thoroughly after handling this material. Do not eat, drink, smoke, or apply cosmetics while handling this material. Avoid breathing vapors or mists generated by this material. Use in a well-ventilated location. Remove contaminated clothing immediately.

STORAGE AND HANDLING PRACTICES: All employees who handle this material should be trained to handle it safely. Keep container tightly closed when not in use. Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Store containers away from incompatible chemicals (see Section 10, Stability and Reactivity). Inspect all incoming containers before storage to ensure containers are properly labeled and not damaged. Empty containers may contain residual liquid or vapors; therefore, empty containers should be handled with care.

SPECIFIC USE(S): These products are for use as an ink. Follow all industry standards for use of these products.

PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: Follow practices indicated in Section 6 (Accidental Release Measures). Make certain that application equipment is locked and tagged-out safely, if necessary. Collect all rinsates and dispose of according to applicable U.S. Federal, State, or local procedures and appropriate Canadian standards.

8. EXPOSURE CONTROLS - PERSONAL PROTECTION

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to ensure exposure levels are maintained below the limits provided in this section. Use local exhaust ventilation. Normal office ventilation conforming to the American Society of Heating, Refrigerating, and Air Conditioning Engineers (ASHRAE) Standards is adequate under normal circumstances of use. Persons using this material should consult a qualified Ventilation Engineer and/or Industrial Hygienist if concerns about exposures arise. If necessary, refer to Australian National Code of Practice for the Control of Workplace Hazardous Substances [NOHSC: 2007 (1994)] for further information. As with all chemicals, ensure proper decontamination equipment (e.g., eyewash/safety shower stations) is available near areas where this material is used as necessary.

EXPOSURE LIMITS/GUIDELINES:

CHEMICAL NAME	CAS #	EXPOSURE LIMITS IN AIR						
		ACGIH-TLVs		OSHA-PELs		NIOSH-RELs		NIOSH
		TWA mg/m ³	STEL mg/m ³	TWA mg/m ³	STEL mg/m ³	TWA mg/m ³	STEL mg/m ³	IDLH mg/m ³
Proprietary Organic Extract		NE	NE	NE	NE	NE	NE	NE
Proprietary Black Pigment		3.5 NIC- 3 (Inhalable fraction)	NE	3.5	NE	3.5 0.1 in presence of PAHs, as PAHs; 10-hr TWA	NE	1750
								DFG MAK: As inhalable dust

NE = Not Established. PAHs = Polycyclic Aromatic Hydrocarbons See Section 16 for Definitions of Other Terms Used

INTERNATIONAL OCCUPATIONAL EXPOSURE LIMITS: The following international limits are in place for some components of these products. Limits may have changed since time of preparation of this MSDS and should be checked with competent authorities of individual countries.

PROPRIETARY BLACK PIGMENT

Mine Safety and Health Administration (MSHA): TWA = 3.5 mg/m³
Australia: TWA = 3 mg/m³, JUL 2008
Belgium: TWA = 3.6 mg/m³, MAR 2002
Denmark: TWA = 3.5 mg/m³, OCT 2002
Finland: TWA = 3.5 mg/m³, STEL = 7 mg/m³, SEP 2009
France: VME = 3.5 mg/m³, FEB 2006

PROPRIETARY BLACK PIGMENT (continued):

Japan: OEL = 1 mg/m³ (respirable), 4 mg/m³ (total), APR 2007
Korea: TWA = 3.5 mg/m³, 2006
Mexico: TWA = 3.5 mg/m³; STEL = 7 mg/m³, 2004
The Netherlands: MAC-TGG = 3.5 mg/m³, 2003
New Zealand: TWA = 3 mg/m³, JAN 2002

8. EXPOSURE CONTROLS - PERSONAL PROTECTION (Continued)

INTERNATIONAL OCCUPATIONAL EXPOSURE LIMITS (continued):

PROPRIETARY BLACK PIGMENT (continued):

Norway: TWA = 3.5 mg/m³, JAN 1999
The Philippines: TWA = 3.5 mg/m³, JAN 1993
Russia: STEL = 4 mg/m³, JUN 2003

PROPRIETARY BLACK PIGMENT (continued):

Sweden: TWA = 3 mg/m³, JUN 2005
United Kingdom: TWA = 3.5 mg/m³; STEL = 7 mg/m³, 2005
In Argentina, Bulgaria, Colombia, Jordan, Singapore, Vietnam check ACGIH TLV

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132), equivalent standards of Canada (including CSA Standard Z94.4-02 and CSA Standard Z94.3-02), standards of EU member states (including EN 529:2005 for respiratory PPE, CEN/TR 15419:2006 for hand protection, and CR 13464:1999 for face/eye protection), or standards of Australia (including AS/NZS 1715:1994 for respiratory PPE, AS/NZS 4501.2:2006 for protective clothing, AS/NZS 2161.1:2000 for glove selection, and AS/NZS 1336:1997 for eye protection). Please reference applicable regulations and standards for relevant details.

RESPIRATORY PROTECTION: Respiratory protection is not generally needed when using these products. Maintain airborne contaminant concentrations below limits listed in this section. In instances where inhalable mists or sprays of product may be generated, and respiratory protection is necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), or equivalent U.S. State standards, Canadian CSA Standard Z94.4-02, the European Standard EN 529:2005, and EU member states, or the Australian Standard 1716-Respiratory Protective Devices, the Australian Standard 1715-Selection, Use, and Maintenance of Respiratory Protective Devices, as well as requirements of Japan. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres, use of a full-facepiece pressure/demand SCBA or a full facepiece, SAR with auxiliary self-contained air supply is required under OSHA's Respiratory Protection Standard (1910.134-1998).

EYE PROTECTION: Depending on the use of these products, splash goggles or safety glasses may be worn. Use goggles or safety glasses for spill response, as stated in Section 6 (Accidental Release Measures) of this MSDS. If necessary, refer to U.S. OSHA 29 CFR 1910.133, the European Standard CR 13464:1999 and the Canadian CSA Standard Z94.3-02, *Industrial Eye and Face Protectors*, the Australian Standard 1337-Eye Protection for Industrial Applications and Australian Standard 1336-Recommended Practices for Eye Protection in the Industrial Environment, as well as requirements of Japan for further information.

HAND PROTECTION: Wear butyl rubber, neoprene, or nitrile rubber or latex gloves for routine use. If necessary, refer to U.S. OSHA 29 CFR 1910.138 appropriate Standards of Canada, the European Standard CEN/TR 15419:2006 or the Australian Standard 2161-Industrial Safety Gloves and Mittens for further information.

BODY PROTECTION: Use body protection appropriate for task, such as a lab coat. If necessary, use body protection appropriate for task (e.g., Tyvek suit, rubber apron). If necessary, refer appropriate Standards of Canada, the European Standard CEN/TR 15419:2006 the to Australian Standard 3765-Clothing for Protection Against Hazardous Chemicals for further information. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection, as described in U.S. OSHA 29 CFR 1910.136 and the Canadian CSA Standard Z195-02, *Protective Footwear*.

9. PHYSICAL and CHEMICAL PROPERTIES

VAPOR DENSITY (air = 1): Not established.

SPECIFIC GRAVITY (water = 1): Not established.

SOLUBILITY IN WATER: Soluble

VAPOR PRESSURE: Not established.

ODOR THRESHOLD: Not established.

COEFFICIENT OF OIL/WATER DISTRIBUTION (PARTITION COEFFICIENT): Not established.

APPEARANCE, ODOR AND COLOR: These products are grey liquids with a mild odor.

HOW TO DETECT THIS SUBSTANCE (warning properties): The odor and color of these products may be distinguishing characteristics.

EVAPORATION RATE (n-BuAc = 1): Not established.

MELTING/FREEZING POINT: Not established.

BOILING POINT: Not established

pH: Not established.

OXIDIZING PROPERTIES: Not an oxidizer.

10. STABILITY and REACTIVITY

STABILITY: Stable under conditions of normal temperature and pressure.

DECOMPOSITION PRODUCTS: *Combustion:* If exposed to extremely high temperatures, these products can decompose to generate carbon oxides. *Hydrolysis:* None known.

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: Strong oxidizers, water-reactive materials.

HAZARDOUS POLYMERIZATION: Will not occur.

OXIDIZING PROPERTIES: Not applicable.

EXPLOSIVE PROPERTIES: Not applicable.

CONDITIONS TO AVOID: Exposure to or contact with extreme temperatures and incompatible chemicals.

PART IV Is there any other useful information about this material?

11. TOXICOLOGICAL INFORMATION

SYMPTOMS OF OVEREXPOSURE BY ROUTE OF EXPOSURE: The most significant routes of occupational overexposure are inhalation and contact with skin and eyes. The symptoms of overexposure to this material, via route of entry, are as described below.

INHALATION: These products do not normally present a significant inhalation hazard under anticipated circumstances of use. Inhalation of vapors, mists, or sprays of this material, may mildly irritate the nose, throat, and other tissues of the respiratory system.

CONTACT WITH SKIN or EYES: Due to the colorants, skin contact may discolor contaminated areas.

11. TOXICOLOGICAL INFORMATION (Continued)

CONTACT WITH SKIN or EYES (continued): Skin contact may cause mild irritation in sensitive individuals. Repeated or prolonged skin overexposure may cause dermatitis (dry, red skin). Eye contact with this material can mildly irritate the eyes, causing discomfort, tearing, and redness. Because the eye tissue may be stained, vision may be temporarily blurred.

SKIN ABSORPTION: The components of these products are not known to be absorbed through intact skin.

INGESTION: Though not anticipated to be a significant route of occupational exposure, ingestion of large quantities of this material may cause nausea, vomiting, diarrhea, and discoloration of the mouth, teeth, and tissues of the throat.

INJECTION: Accidental injection of this liquid (as may occur by a puncture with a contaminated object) will cause local pain, irritation, and redness.

HEALTH EFFECTS OR RISKS FROM EXPOSURE: An Explanation in Lay Terms. In the event of overexposure, the following symptoms may be observed:

ACUTE: The ink may stain hair, skin, and other contaminated tissue. Acute exposure to this material via skin contact, eye contact, and inhalation may mildly irritate contaminated tissue. Ingestion of large amounts may cause nausea, vomiting, diarrhea.

HEALTH EFFECTS OR RISKS FROM EXPOSURE (continued):

CHRONIC: Repeated or prolonged skin overexposure may cause dermatitis (dry, red skin).

TARGET ORGANS: ACUTE: Skin, respiratory system, eyes. CHRONIC: Skin.

TOXICITY DATA: Specific toxicology data currently available for components of these products listed in Section 3 (Composition and Information on Ingredients) by CAS # are as follows.

PROPRIETARY BLACK PIGMENT:

LD₅₀ (Oral-Rat) > 15 400 mg/kg: Behavioral: somnolence (general depressed activity)

LD₅₀ (Skin-Rabbit) > 3 gm/kg

TCLo (Inhalation-Rat) 7 mg/m³: Lungs, Thorax, or Respiration: other changes; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TCLo (Inhalation-Rat) 1.66 mg/m³/7 hours: Lungs, Thorax, or Respiration: sputum; Blood: changes in leukocyte (WBC) count; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TCLo (Inhalation-Rat) 50 mg/m³: Sense Organs and Special Senses (Olfaction): effect, not otherwise specified; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TCLo (Inhalation-Rat) 229 mg/m³/6 hours: Lungs, Thorax, or Respiration: other changes; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TCLo (Inhalation-Rat) 50 mg/m³/6 hours/90 days-intermittent: Lungs, Thorax, or Respiration: other changes

TCLo (Inhalation-Rat) 1 mg/m³/13 weeks-intermittent: Lungs, Thorax, or Respiration - other changes; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TCLo (Inhalation-Rat) 1 mg/m³/13 weeks-intermittent: Lungs, Thorax, or Respiration: other changes, changes in lung weight; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TCLo (Inhalation-Rat) 50 mg/m³/13 weeks-intermittent: Lungs, Thorax, or Respiration: other changes; Biochemical: Metabolism (Intermediary): other

TCLo (Inhalation-Rat) 50 mg/m³/13 weeks-intermittent: Lungs, Thorax, or Respiration: other changes; Biochemical: Metabolism (Intermediary): other, Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TCLo (Inhalation-Rat) 7 mg/m³/6 hours/13 weeks-intermittent: Sense Organs and Special Senses (Olfaction): effect, not otherwise specified; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TCLo (Inhalation-Rat) 11,600 µg/m³/18 hours/2 years-intermittent: Tumorigenic: carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration: tumors

TCLo (Inhalation-Mouse) 50 mg/m³/6 hours: Sense Organs and Special Senses (Olfaction): effect, not otherwise specified

TCLo (Inhalation-Mouse) 1 mg/m³/13 weeks-intermittent: Lungs, Thorax, or Respiration: other changes; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TCLo (Inhalation-Mouse) 1 mg/m³/13 weeks-intermittent: Lungs, Thorax, or Respiration: other changes, changes in lung weight; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TCLo (Inhalation-Mouse) 7 mg/m³/6 hours/13 weeks-intermittent: Sense Organs and Special Senses (Olfaction): effect, not otherwise specified; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TCLo (Inhalation-Hamster) 7 mg/m³/13 weeks-intermittent: Lungs, Thorax, or Respiration: other changes; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

CARCINOGENIC POTENTIAL OF COMPONENTS: Components of these products are listed by agencies tracking the carcinogenic potential of chemical compounds, as follows;

PROPRIETARY BLACK PIGMENT: ACGIH TLV-A4 (Not Classifiable as a Human Carcinogen), IARC-2B (Possibly Carcinogenic to Humans); MAK-3B (Substances for Which *in vitro* tests or Animal Studies Have Yielded Evidence Of Carcinogenic Effects That is Not Sufficient for Classification of the Substance In One of the Other Categories. Further studies are required before a final classification can be made. A MAK or BAT value can be established, provided no genotoxic effects have been detected.); NIOSH-Ca (Potential Occupational Carcinogen with No Further Categorization * In presence of PAHs); Notice of Intended Change: ACGIH TLV-A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)



HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HEALTH HAZARD	(BLUE)	1
---------------	--------	---

FLAMMABILITY HAZARD	(RED)	0
---------------------	-------	---

PHYSICAL HAZARD	(YELLOW)	0
-----------------	----------	---

PROTECTIVE EQUIPMENT

EYES	RESPIRATORY	HANDS	BODY
	SEE SECTION 8		SEE SECTION 8

For Routine Industrial Use and Handling Applications

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate
3 = Serious 4 = Severe * = Chronic hazard

PROPRIETARY BLACK PIGMENT (continued):

TCLo (Inhalation-Hamster) 50 mg/m³/6 hours/13 weeks-intermittent: Sense Organs and Special Senses (Olfaction): effect, not otherwise specified

TDLo (Oral-Mouse) 20,000 µg/kg/4 weeks-intermittent: Brain and Coverings: other degenerative changes; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TDLo (Skin-Rat) 11 gm/kg/4 weeks-intermittent: Blood: pigmented or nucleated red blood cells; Liver: changes in liver weight; Nutritional and Gross Metabolic: weight loss or decreased weight gain

TDLo (Intravenous-Rat) 10 mg/kg/2 minutes: Liver: changes in liver weight; Blood: changes in spleen

TDLo (Intravenous-Rat) 10 mg/kg/2 minutes: Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: hepatic microsomal mixed oxidase (dealkylation, hydroxylation, etc.)

TDLo (Intratracheal-Rat) 16 mg/kg: Lungs, Thorax, or Respiration: other changes; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TDLo (Intratracheal-Rat) 15 mg/kg: Lungs, Thorax, or Respiration: other changes; Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: cytochrome oxidases (including oxidative phosphorylation)

TDLo (Intratracheal-Rat) 10 mg/kg: Lungs, Thorax, or Respiration: sputum; Biochemical: Metabolism (Intermediary): other proteins; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TDLo (Intratracheal-Mouse) 1000 µg/kg: Lungs, Thorax, or Respiration: other changes; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TDLo (Intratracheal-Mouse) 20 mg/kg/4 days-intermittent: Lungs, Thorax, or Respiration: sputum; Immunological Including Allergic: increase in cellular immune response; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TDLo (Intratracheal-Mouse) 4000 µg/kg/4 weeks-intermittent: Lungs, Thorax, or Respiration: other changes; Immunological Including Allergic: increase in cellular immune response; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TDLo (Parenteral-Mouse) 36 µg/kg/3 days-intermittent: Immunological Including Allergic: increase in humoral immune response

Mutation in Microorganisms (Bacteria-Salmonella typhimurium) 1 mg/plate

DNA Adduct (Inhalation-Mouse) 6200 µg/m³/16 hours/12 weeks-intermittent

DNA Damage (Human Lymphocyte) 16 µg/L/48 hours

DNA Damage (Inhalation-Rat) 50 µg/L/13 weeks-intermittent

DNA Damage (Inhalation-Rat) 50 µg/L/13 weeks

PROPRIETARY ORGANIC EXTRACT:

TDLo (Subcutaneous-Rat) 2920 mg/kg/73 weeks-intermittent: Tumorigenic: equivocal tumorigenic agent by RTECS criteria, tumors at site of application

Mutation in Microorganisms (Bacteria-Salmonella typhimurium) 5 mg/plate

11. TOXICOLOGICAL INFORMATION (Continued)

CARCINOGENIC POTENTIAL OF COMPONENTS (continued): The remaining components of these products listed in Section 3 (Composition and Information on Ingredients) by CAS # are not found on the following lists: U.S. EPA, U.S. NTP, U.S. OSHA, U.S. NIOSH, GERMAN MAK, IARC, and ACGIH, and therefore are neither considered to be nor suspected to be cancer-causing agents by these agencies.

IRRITANCY OF PRODUCT: Acute exposure to this material via skin contact, eye contact, and inhalation may mildly irritate contaminated tissue.

SENSITIZATION TO THE PRODUCT: The components of this product are not known to be human respiratory or skin sensitizers.

REPRODUCTIVE TOXICITY INFORMATION: Listed below is information concerning the effects of components of these products listed in Section 3 (Composition and Information on Ingredients) by CAS # on the human reproductive system.

Mutagenicity: The components of these products are not reported to produce mutagenic effects in humans. The Proprietary Organic Extract component of these products was evaluated for the induction of sex-linked recessive lethal mutations in *Drosophila melanogaster* by the National Toxicology Program. Canton-S wild-type males were treated with concentrations of the extract that result in approximately 30% mortality. Following treatment, males were mated individually to 3 harems of Basc virgin females to produce 3 broods for analysis. The concentrations of this material tested by injection (500,000 ppm) or feeding (500,000 ppm) were negative in this assay.

Embryotoxicity: The components of these products are not reported to produce embryotoxic effects in humans.

Teratogenicity: The components of these products are not reported to cause teratogenic effects in humans.

Reproductive Toxicity: The components of these products are not reported to cause reproductive effects in humans.

A mutagen is a chemical that causes permanent changes to genetic material (DNA) such that the changes will propagate through generational lines. An embryotoxin is a chemical that causes damage to a developing embryo (i.e. within the first eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A teratogen is a chemical that causes damage to a developing fetus, but the damage does not propagate across generational lines. A reproductive toxin is any substance that interferes in any way with the reproductive process.

BIOLOGICAL EXPOSURE INDICES: Currently, there are no Biological Exposure Indices (BEIs) established for the components of these products.

12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

MOBILITY: These products have not been tested for mobility in soil. It is expected to be mobile in soil.

PERSISTENCE AND BIODEGRADABILITY: These products have not been tested for persistence or biodegradability. It is expected that some biodegradation will occur to these products; however, no specific information is known.

BIO-ACCUMULATION POTENTIAL: These products have not been tested for bio-accumulation potential.

ECOTOXICITY: These products have not been tested for the effects of these products on terrestrial or aquatic organisms if released to the environment. Plants may be discolored and damaged (depending on the severity of the contamination).

OTHER ADVERSE EFFECTS: These products do not contain any component with known ozone depletion potential.

ENVIRONMENTAL EXPOSURE CONTROLS: Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS: It is the responsibility of the generator to determine at the time of disposal whether the product meets the criteria of a hazardous waste per regulations of the area in which the waste is generated and/or disposed of. Waste disposal must be in accordance with appropriate Federal, State, and local regulations. These products, if unaltered by use, may be disposed of by treatment at a permitted facility or as advised by your local hazardous waste regulatory authority. Shipment of wastes must be done with appropriately permitted and registered transporters.

DISPOSAL CONTAINERS: Waste materials must be placed in and shipped in appropriate 5-gallon or 55-gallon poly or metal waste pails or drums. Permeable cardboard containers are not appropriate and should not be used. Ensure that any required marking or labeling of the containers be done to all applicable regulations.

PRECAUTIONS TO BE FOLLOWED DURING WASTE HANDLING: Wear proper protective equipment when handling waste materials.

U.S. EPA WASTE NUMBER: Not applicable to wastes consisting only of these products.

EUROPEAN WASTE CODES: Wastes from MFSU and Removal of Printing Inks: 08 03 99: Wastes Not Otherwise Specified

14. TRANSPORTATION INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION: These products are not classified as dangerous goods, per U.S. DOT regulations, under 49 CFR 172.101.

TRANSPORT CANADA, TRANSPORTATION OF DANGEROUS GOODS REGULATIONS: These products are NOT classified as dangerous goods, per regulations of Transport Canada.

INTERNATIONAL AIR TRANSPORT ASSOCIATION SHIPPING INFORMATION (IATA): These products are NOT classified as dangerous goods.

INTERNATIONAL MARITIME ORGANIZATION SHIPPING INFORMATION (IMO): These products are NOT classified as dangerous goods.

EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD (ADR): These products are NOT classified by the United Nations Economic Commission for Europe to be dangerous goods.

14. TRANSPORTATION INFORMATION (Continued)

AUSTRALIAN FEDERAL OFFICE OF ROAD SAFETY CODE FOR THE TRANSPORTATION OF DANGEROUS GOODS BY ROAD OR RAIL: These products are NOT classified as dangerous goods, per regulations of the Australian Federal Office of Road Safety.

15. REGULATORY INFORMATION

ADDITIONAL UNITED STATES REGULATIONS:

U.S. SARA REPORTING REQUIREMENTS: The components of these products listed in Section 3 (Composition and Information on Ingredients) by CAS # are not subject to the reporting requirements of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act.

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for this material. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): Not applicable.

U.S. TSCA INVENTORY STATUS: The components of these products listed in Section 3 (Composition and Information on Ingredients) by CAS # are listed on the TSCA Inventory.

U.S. HAZARDOUS AIR POLLUTANT (HAPs): The components of these products listed in Section 3 (Composition and Information on Ingredients) by CAS # are not listed by the EPA under section 112(b) of the Clean Air Act as a 'HAP'.

OTHER U.S. FEDERAL REGULATIONS: Not applicable.

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): The Proprietary Black Pigment component, (airborne, unbound particles of respirable size) is on the California Proposition 65 Lists. If airborne particles of this product are generated, the following warning must be on packaging and labeling of this product: **WARNING!** This product contains a component known to the State of California to cause cancer. As a liquid, this warning is not expected to be required.

ANSI LABELING (Z129.1): **CAUTION!** MAY CAUSE MILD SKIN, EYE, AND RESPIRATORY TRACT IRRITATION. MAY DISCOLOR CONTAMINATED SKIN, EYES, HAIR, AND CLOTHES. Use with adequate ventilation. Avoid contact of liquid with skin, eyes, and clothing. Avoid exposure to vapors, mists, or sprays. Wash thoroughly after handling. Wear appropriate hand and eye protection. **FIRST-AID:** In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. If inhaled, remove to fresh air. If swallowed, do not induce vomiting. Get medical attention if irritation develops or persists or if any other adverse effect occurs. **IN CASE OF FIRE:** Use water fog, dry chemical, or CO₂, or alcohol foam. **IN CASE OF SPILL:** Absorb spill with inert materials (e.g., polypads, dry sand). Rinse area with soapy water. Consult Material Safety Data Sheet for additional information.

ADDITIONAL CANADIAN REGULATIONS:

CANADIAN DSL/NDL INVENTORY STATUS: The components of these products listed in Section 3 (Composition and Information on Ingredients) by CAS # are listed on the DSL Inventory.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITY SUBSTANCES LISTS: The components of these products listed in Section 3 (Composition and Information on Ingredients) by CAS # are not on the CEPA Priority Substances Lists.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: Not applicable.

ADDITIONAL EUROPEAN UNION REGULATIONS:

GLOBAL HARMONIZATION AND EU CLP REGULATION (EC) 1272/2008 LABELING AND CLASSIFICATION: Classified in accordance with CLP Regulation (EC) 1272/2008. For additional information on classification under (67/548/EEC), see below.

Classification: Not Applicable

Hazard Statements: Not Applicable

Prevention Precautionary Statements: Not Applicable

Response Precautionary Statements: Not Applicable

Storage Precautionary Statements: Not Applicable

Disposal Precautionary Statements: Not Applicable

Signal Word: Not Applicable

Hazard Symbol: Not Applicable

EU LABELING/CLASSIFICATION UNDER 67/548/EEC AND 2001/59/EC: These products have been classified per criteria of European Union Council Directives 67/548/EEC and 2001/59/EC.

EU Classification: Not Applicable

EU Risk Phrases: Not Applicable

EU Safety Phrases: Not Applicable

European Community Annex II Hazard Symbols: Not Applicable

LABELING AND CLASSIFICATION FOR COMPONENTS:

UNDER CLP REGULATION (EC) 1272/2008

Proprietary Black Pigment: An official classification for this substance has not been published under CLP 1272/2008. This is a self-classification.

Classification: Carcinogenic Category 2

Hazard Statements: H351: Suspected of causing cancer by inhalation.

Precautionary Statements:

Prevention: P201: Obtain special instructions before use. P202: Do not handle until all safety precautions have been read and understood. P281: Use personal protective equipment as needed.

Response Precautionary Statements: P308 + P313: IF exposed or concerned: Get medical advice/attention.

Storage: P405: Store locked up.

Disposal: P501: Dispose of contents/containers in accordance with all local, regional, national and international regulations.

Signal Word: Warning

Hazard Symbol: GHS08

All Remaining Components:

Classification: An official classification for this substance has not been published under CLP 1272/2008.

15. REGULATORY INFORMATION (Continued)

ADDITIONAL EUROPEAN UNION REGULATIONS (continued):

LABELING AND CLASSIFICATION FOR COMPONENTS (continued):

UNDER 67/548/EEC AND 2001/59/EC

Proprietary Black Pigment: An official classification for this substance has not been published in Commission Directives 93/72/EEC or 94/69EC. This is a self-classification.

Classification: Carcinogenic Cat. 3

Risk Phrases: [R: 40]: Limited evidence of a carcinogenic effect.

Safety Phrases: [S: 22]: Do not breathe dust. [S: 38]: In case of insufficient ventilation wear suitable respiratory equipment. [S: 53]: Avoid exposure - obtain special instructions before use.

All Remaining Components:

Classification: An official classification for this substance has not been published in Commission Directives 93/72/EEC or 94/69EC.

ADDITIONAL AUSTRALIAN REGULATIONS:

AUSTRALIAN INVENTORY OF CHEMICAL SUBSTANCES (AICS) STATUS: The components of these products listed in Section 3 (Composition and Information on Ingredients) by CAS # are listed on the AICS.

HAZARDOUS SUBSTANCES INFORMATION SYSTEM (HSIS): The components of these products listed in Section 3 (Composition and Information on Ingredients) by CAS # are not listed in the HSIS.

STANDARD FOR THE UNIFORM SCHEDULING OF DRUGS AND POISONS: Not applicable.

LABELING AND CLASSIFICATION: These products do not meet the definition of any hazard class, based a review of the regulation [NOHSC: 10005 (1994)].

16. OTHER INFORMATION

PREPARED BY:

CHEMICAL SAFETY ASSOCIATES, Inc.
PO Box 1961, Hilo, HI 96721 • 800/441-3365

DATE OF PRINTING:

October 20, 2010

The data in this Material Safety Data Sheet is true and accurate to the best of Silverback Ink Corp's knowledge. However, since data, safety standards, and government regulations are subject to change conditions of handling, use, or misuse are beyond Silverback Ink Corp's control, Silverback Ink Corp MAKES NO WARRANTY, EITHER EXPRESSED OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. The user is required to comply with all laws and regulations relating to the purchase, use, storage, and disposal of the product. User must be familiar with and follow generally accepted safe handling procedures of chemicals, and is solely responsible for any effects caused by its misuse or mixing of this chemical with any other substance.

DEFINITIONS OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these, which are commonly used, include the following:

CAS #: This is the Chemical Abstract Service Number that uniquely identifies each constituent.

EXPOSURE LIMITS IN AIR:

CEILING LEVEL: The concentration that shall not be exceeded during any part of the working exposure.

DFG MAK Germ Cell Mutagen Categories: 1: Germ cell mutagens which have been shown to increase the mutant frequency in the progeny of exposed humans. 2: Germ cell mutagens which have been shown to increase the mutant frequency in the progeny of exposed mammals. 3A: Substances which have been shown to induce genetic damage in germ cells of human of animals, or which produce mutagenic effects in somatic cells of mammals *in vivo* and have been shown to reach the germ cells in an active form. 3B: Substances which are suspected of being germ cell mutagens because of their genotoxic effects in mammalian somatic cell *in vivo*; in exceptional cases, substances for which there are no *in vivo* data, but which are clearly mutagenic *in vitro* and structurally related to known *in vivo* mutagens. 4: Not applicable (Category 4 carcinogenic substances are those with non-genotoxic mechanisms of action. By definition, germ cell mutagens are genotoxic. Therefore, a Category 4 for germ cell mutagens cannot apply. At some time in the future, it is conceivable that a Category 4 could be established for genotoxic substances with primary targets other than DNA [e.g. purely aneugenic substances] if research results make this seem sensible.) 5: Germ cell mutagens, the potency of which is considered to be so low that, provided the MAK value is observed, their contribution to genetic risk for humans is expected not to be significant.

DFG MAK Pregnancy Risk Group Classification: **Group A:** A risk of damage to the developing embryo or fetus has been unequivocally demonstrated. Exposure of pregnant women can cause damage of the developing organism, even when MAK and BAT (Biological Tolerance Value for Working Materials) values are observed. **Group B:** Currently available information indicates a risk of damage to the developing embryo or fetus must be considered to be probable. Damage to the developing organism cannot be excluded when pregnant women are exposed, even when MAK and BAT values are observed. **Group C:** There is no reason to fear a risk of damage to the developing embryo or fetus when MAK and BAT values are observed. **Group D:** Classification in one of the groups A-C is not yet possible because, although the data available may indicate a trend, they are not sufficient for final evaluation.

IDLH-Immediately Dangerous to Life and Health: This level represents a concentration from which one can escape within 30-minutes without suffering escape-preventing or permanent injury.

LOQ: Limit of Quantitation.

MAK: Federal Republic of Germany Maximum Concentration Values in the workplace.

NE: Not Established. When no exposure guidelines are established, an entry of NE is made for reference.

NIC: Notice of Intended Change.

NIOSH CEILING: The exposure that shall not be exceeded during any part of the workday. If instantaneous monitoring is not feasible, the ceiling shall be assumed as a 15-minute TWA exposure (unless otherwise specified) that shall not be exceeded at any time during a workday.

NIOSH RELs: NIOSH's Recommended Exposure Limits.

PEL-Permissible Exposure Limit: OSHA's Permissible Exposure Limits. This exposure value means exactly the same as a TLV, except that it is enforceable by OSHA. The OSHA Permissible Exposure Limits are based in the 1989 PELs and the June, 1993 Air Contaminants Rule (Federal Register: 58: 35338-35351 and 58: 40191). Both the current PELs and the vacated PELs are indicated. The phrase, "Vacated 1989 PEL," is placed next to the PEL that was vacated by Court Order.

SKIN: Used when there is a danger of cutaneous absorption.

STEL-Short Term Exposure Limit: Short Term Exposure Limit, usually a 15-minute time-weighted average (TWA) exposure that should not be exceeded at any time during a workday, even if the 8-hr TWA is within the TLV-TWA, PEL-TWA or REL-TWA.

TLV-Threshold Limit Value: An airborne concentration of a substance that represents conditions under which it is generally believed that nearly all workers may be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour.

TWA-Time Weighted Average: Time Weighted Average exposure concentration for a conventional 8-hr (TLV, PEL) or up to a 10-hr (REL) workday and a 40-hr workweek.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD

RATINGS: This rating system was developed by the National Paint and Coating Association and has been adopted by industry to identify the degree of chemical hazards.

HEALTH HAZARD: 0 (Minimal Hazard): No significant health risk, irritation of skin or eyes not anticipated. *Skin Irritation:* Essentially non-irritating. *PII or Draize = "0".* *Eye Irritation:* Essentially non-irritating, or minimal effects which clear in < 24 hours [e.g. mechanical irritation]. *Draize = "0".* *Oral Toxicity LD₅₀ Rat:* < 5000 mg/kg. *Dermal Toxicity LD₅₀ Rat or Rabbit:* < 2000 mg/kg. *Inhalation Toxicity 4-hrs LC₅₀ Rat:* < 20 mg/L; 1 (Slight Hazard): Minor reversible injury may occur; slightly or mildly irritating. *Skin Irritation:* Slightly or mildly irritating. *Eye Irritation:* Slightly or mildly irritating. *Oral Toxicity LD₅₀ Rat:* > 500-5000 mg/kg. *Dermal Toxicity LD₅₀ Rat or Rabbit:* > 1000-2000 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* > 2-20 mg/L; 2 (Moderate Hazard): Temporary or transitory injury may occur. *Skin Irritation:* Moderately irritating; primary irritant; sensitizer. *PII or Draize > 0, < 5.* *Eye Irritation:* Moderately to severely irritating and/or corrosive; reversible corneal opacity; corneal involvement or irritation clearing in 8-21 days. *Draize > 0, ≤ 25.* *Oral Toxicity LD₅₀ Rat:* > 50-500 mg/kg. *Dermal Toxicity LD₅₀ Rat or Rabbit:* > 200-1000 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* > 0.5-2 mg/L; 3 (Serious Hazard): Major injury likely unless prompt action is taken and medical treatment is given; high level of toxicity; corrosive. *Skin Irritation:* Severely irritating and/or corrosive; may destroy dermal tissue, cause skin burns, dermal necrosis. *PII or Draize > 5-8* with destruction of tissue. *Eye Irritation:* Corrosive, irreversible destruction of ocular tissue; corneal involvement or irritation persisting for more than 21 days. *Draize > 80* with effects irreversible in 21 days. *Oral Toxicity LD₅₀ Rat:* > 1-50 mg/kg. *Dermal Toxicity LD₅₀ Rat or Rabbit:* > 20-200 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* > 0.05-0.5 mg/L; 4 (Severe Hazard): Life-threatening; major or permanent damage may result from single or repeated exposure. *Skin Irritation:* Not appropriate. Do not rate as a "4", based on skin irritation alone. *Eye Irritation:* Not appropriate. Do not rate as a "4", based on eye irritation alone. *Oral Toxicity LD₅₀ Rat:* ≤ 1 mg/kg. *Dermal Toxicity LD₅₀ Rat or Rabbit:* ≤ 20 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* ≤ 0.05 mg/L.

FLAMMABILITY HAZARD: 0 (Minimal Hazard-Materials that will not burn in air when exposure to a temperature of 815.5°C [1500°F] for a period of 5 minutes.); 1 (Slight Hazard-Materials that must be pre-heated before ignition can occur. Material require considerable pre-heating, under all ambient temperature conditions before ignition and combustion can occur, including: Materials that will burn in air when exposed to a temperature of 815.5°C (1500°F) for a period of 5 minutes or less; Liquids, solids and semisolids having a flash point at or above 93.3°C [200°F] (e.g. OSHA Class IIIB, or; Most ordinary combustible materials [e.g. wood, paper, etc.]; 2 (Moderate Hazard-Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not, under normal conditions, form hazardous atmospheres in air, but under high ambient temperatures or moderate heating may release vapor in sufficient quantities to produce hazardous atmospheres in air, including: Liquids having a flash-point at or above 37.8°C [100°F]; Solid materials in the form of course dusts that may burn rapidly but that generally do not form explosive atmospheres; Solid materials in a fibrous or shredded form that may burn rapidly and create flash fire hazards (e.g. cotton, sisal, hemp; Solids and semisolids that readily give off flammable vapors.); 3 (Serious Hazard- Liquids and solids that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures, or, unaffected by ambient temperature, are readily ignited under almost all conditions, including: Liquids having a flash point below 22.8°C [73°F] and having a boiling point at or above 38°C [100°F] and below 37.8°C [100°F] [e.g. OSHA Class IB and IC]; Materials that on account of their physical form or environmental conditions can form explosive mixtures with air and are readily dispersed in air [e.g., dusts of combustible solids, mists or droplets of flammable liquids]; Materials that burn extremely rapidly, usually by reason of self-contained oxygen [e.g. dry nitrocellulose and many organic peroxides]; 4 (Severe Hazard-Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air, and which will burn readily, including: Flammable gases; Flammable cryogenic materials; Any liquid or gaseous material that is liquid while under pressure and has a flash point below 22.8°C [73°F] and a boiling point below 37.8°C [100°F] [e.g. OSHA Class IA; Material that ignite spontaneously when exposed to air at a temperature of 54.4°C [130°F] or below [e.g. pyrophoric].

DEFINITIONS OF TERMS (Continued)

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS (continued):

PHYSICAL HAZARD: 0 (*Water Reactivity*: Materials that do not react with water. *Organic Peroxides*: Materials that are normally stable, even under fire conditions and will not react with water. *Explosives*: Substances that are Non-Explosive. *Unstable Compressed Gases*: No Rating. *Pyrophorics*: No Rating. *Oxidizers*: No "0" rating allowed. *Unstable Reactives*: Substances that will not polymerize, decompose, condense or self-react.); **1** (*Water Reactivity*: Materials that change or decompose upon exposure to moisture. *Organic Peroxides*: Materials that are normally stable, but can become unstable at high temperatures and pressures. These materials may react with water, but will not release energy. *Explosives*: Division 1.5 & 1.6 substances that are very insensitive explosives or that do not have a mass explosion hazard. *Compressed Gases*: Pressure below OSHA definition. *Pyrophorics*: No Rating. *Oxidizers*: Packaging Group III; *Solids*: any material that in either concentration tested, exhibits a mean burning time less than or equal to the mean burning time of a 3:7 potassium bromate/cellulose mixture and the criteria for Packing Group I and II are not met. *Liquids*: any material that exhibits a mean pressure rise time less than or equal to the pressure rise time of a 1:1 nitric acid (65%)/cellulose mixture and the criteria for Packing Group I and II are not met. *Unstable Reactives*: Substances that may decompose, condense or self-react, but only under conditions of high temperature and/or pressure and have little or no potential to cause significant heat generation or explosive hazard. Substances that readily undergo hazardous polymerization in the absence of inhibitors.); **2** (*Water Reactivity*: Materials that may react violently with water. *Organic Peroxides*: Materials that, in themselves, are normally unstable and will readily undergo violent chemical change, but will not detonate. These materials may also react violently with water. *Explosives*: Division 1.4 – Explosive substances where the explosive effect are largely confined to the package and no projection of fragments of appreciable size or range are expected. An external fire must not cause virtually instantaneous explosion of almost the entire contents of the package. *Compressed Gases*: Pressurized and meet OSHA definition but < 514.7 psi absolute at 21.1°C (70°F) [500 psig]. *Pyrophorics*: No Rating. *Oxidizers*: Packaging Group II; *Solids*: any material that, either in concentration tested, exhibits a mean burning time of less than or equal to the mean burning time of a 2:3 potassium bromate/cellulose mixture and the criteria for Packing Group I are not met. *Liquids*: any material that exhibits a mean pressure rise time less than or equal to the pressure rise of a 1:1 aqueous sodium chlorate solution (40%)/cellulose mixture and the criteria for Packing Group I are not met. *Unstable Reactives*: Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure, but have a low potential for significant heat generation or explosion. Substances that readily form peroxides upon exposure to air or oxygen at room temperature); **3** (*Water Reactivity*: Materials that may form explosive reactions with water. *Organic Peroxides*: Materials that are capable of detonation or explosive reaction, but require a strong initiating source, or must be heated under confinement before initiation; or materials that react explosively with water. *Explosives*: Division 1.2 – Explosive substances that have a fire hazard and either a minor blast hazard or a minor projection hazard or both, but do not have a mass explosion hazard. *Compressed Gases*: Pressure ≥ 514.7 psi absolute at 21.1°C (70°F) [500 psig]. *Pyrophorics*: No Rating. *Oxidizers*: Packaging Group I; *Solids*: any material that, in either concentration tested, exhibits a mean burning time less than the mean burning time of a 3:2 potassium bromate/cellulose mixture. *Liquids*: Any material that spontaneously ignites when mixed with cellulose in a 1:1 ratio, or which exhibits a mean pressure rise time less than the pressure rise time of a 1:1 perchloric acid (50%)/cellulose mixture. *Unstable Reactives*: Substances that may polymerize, decompose, condense or self-react at ambient temperature and/or pressure and have a moderate potential to cause significant heat generation or explosion.); **4** (*Water Reactivity*: Materials that react explosively with water without requiring heat or confinement. *Organic Peroxides*: Materials that are readily capable of detonation or explosive decomposition at normal temperature and pressures. *Explosives*: Division 1.1 & 1.2-explosive substances that have a mass explosion hazard or have a projection hazard. A mass explosion is one that affects almost the entire load instantaneously. *Compressed Gases*: No Rating. *Pyrophorics*: Add to the definition of Flammability "4". *Oxidizers*: No "4" rating. *Unstable Reactives*: Substances that may polymerize, decompose, condense or self-react at ambient temperature and/or pressure and have a high potential to cause significant heat generation or explosion.).

NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS:

HEALTH HAZARD: 0 (materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials): Gases and vapors whose LC₅₀ for acute inhalation toxicity is greater than 10,000 ppm. Dusts and mists whose LC₅₀ for acute inhalation toxicity is greater than 200 mg/L. Materials whose LD₅₀ for acute dermal toxicity is greater than 2000 mg/kg. Materials whose LD₅₀ for acute oral toxicity is greater than 2000 mg/kg. Materials that are essentially non-irritating to the respiratory tract, eyes and skin. **1** (materials that, under emergency conditions, can cause significant irritation): Gases and vapors whose LC₅₀ for acute inhalation toxicity is greater than 5,000 ppm but less than or equal to 10,000 ppm. Dusts and mists whose LC₅₀ for acute inhalation toxicity is greater than 10 mg/L but less than or equal to 200 mg/L. Materials whose LD₅₀ for acute dermal toxicity is greater than 1000 mg/kg but less than or equal to 2000 mg/kg. Materials whose LD₅₀ for acute oral toxicity is greater than 500 mg/kg but less than or equal to 2000 mg/kg. Materials that cause slight to moderate irritation to the respiratory tract, eyes and skin. **2** (materials that, under emergency conditions, can cause temporary incapacitation or residual injury): Gases and vapors whose LC₅₀ for acute inhalation toxicity is greater than 3,000 ppm but less than or equal to 5,000 ppm. Dusts and mists whose LC₅₀ for acute inhalation toxicity is greater than 2 mg/L but less than or equal to 10 mg/L. Materials whose LD₅₀ for acute dermal toxicity is greater than 200 mg/kg but less than or equal to 1000 mg/kg. Materials whose LD₅₀ for acute oral toxicity is greater than 50 mg/kg but less than or equal to 500 mg/kg. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than one-fifth its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 5000 ppm and that does not meet the criteria for either degree of hazard 3 or degree of hazard 4. Compressed liquefied gases with boiling points between -30°C (-22°F) and -55°C (-66.5°F) that cause severe tissue damage, depending on duration of exposure. Materials that are respiratory irritants. Materials that cause severe, but reversible irritation to the eyes or are lachrymators. Materials that are primary skin irritants or sensitizers. **3** (materials that, under emergency conditions, can cause serious or permanent injury): Gases and vapors whose LC₅₀ for acute inhalation toxicity is greater than 1,000 ppm but less than or equal to 3,000 ppm. Dusts and mists whose LC₅₀ for acute inhalation toxicity is greater than 0.5 mg/L but less than or equal to 2 mg/L.

NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS (continued):

HEALTH HAZARD (continued): 3 (continued): Materials whose LD₅₀ for acute dermal toxicity is greater than 40 mg/kg but less than or equal to 200 mg/kg. Materials whose LD₅₀ for acute oral toxicity is greater than 5 mg/kg but less than or equal to 50 mg/kg. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than one-fifth its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 3000 ppm and that does not meet the criteria for degree of hazard 4. Compressed liquefied gases with boiling points between -30°C (-22°F) and -55°C (-66.5°F) that cause frostbite and irreversible tissue damage. Materials that are respiratory irritants. Cryogenic gases that cause frostbite and irreversible tissue damage. Materials that are corrosive to the respiratory tract. Materials that are corrosive to the eyes or cause irreversible corneal opacity. Materials that are corrosive to the skin. **4** (materials that, under emergency conditions, can be lethal): Gases and vapors whose LC₅₀ for acute inhalation toxicity less than or equal to 1,000 ppm. Dusts and mists whose LC₅₀ for acute inhalation toxicity is less than or equal to 0.5 mg/L. Materials whose LD₅₀ for acute dermal toxicity is less than or equal to 40 mg/kg. Materials whose LD₅₀ for acute oral toxicity is less than or equal to 5 mg/kg. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than one-fifth its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 1000 ppm.

FLAMMABILITY HAZARD: 0 Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand: Materials that will not burn in air when exposed to a temperature of 816°C (1500°F) for a period of 5 minutes in accordance with Annex D. **1** Materials that must be preheated before ignition can occur. Materials in this degree require considerable preheating, under all ambient temperature conditions, before ignition and combustion can occur: Materials that will burn in air when exposed to a temperature of 816°C (1500°F) for a period of 5 minutes in accordance with Annex D. Liquids, solids and semisolids having a flash point at or above 93.4°C (200°F) (i.e. Class IIIB liquids). Liquids with a flash point greater than 35°C (95°F) that do not sustain combustion when tested using the Method of Testing for Sustained Combustibility, per 49 CFR 173, Appendix H or the UN Recommendation on the Transport of Dangerous Goods, Model Regulations (current edition) and the related Manual of Tests and Criteria (current edition). Liquids with a flash point greater than 35°C (95°F) in a water-miscible solution or dispersion with a water non-combustible liquid/solid content of more than 85 percent by weight. Liquids that have no fire point when tested by ASTM D 92 Standard Test Method for Flash and Fire Points by Cleveland Open Cup, up to a boiling point of the liquid or up to a temperature at which the sample being tested shows an obvious physical change. Combustible pellets with a representative diameter of greater than 2 mm (10 mesh). Solids containing greater than 0.5 percent by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. Most ordinary combustible materials. **2** Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not under normal conditions form hazardous atmospheres with air, but under high ambient temperatures or under moderate heating could release vapor in sufficient quantities to produce hazardous atmospheres with air: Liquids having a flash point at or above 37.8°C (100°F) and below 93.4°C (200°F) (i.e. Class II and Class IIIA liquids.) Solid materials in the form of powders or coarse dusts of representative diameter between 420 microns (40 mesh) and 2 mm (10 mesh) that burn rapidly but that generally do not form explosive mixtures in air. Solid materials in fibrous or shredded form that burn rapidly and create flash fire hazards, such as cotton, sisal and hemp. Solids and semisolids that readily give off flammable vapors. Solids containing greater than 0.5 percent by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. **3** Liquids and solids that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures or, though unaffected by ambient temperatures, are readily ignited under almost all conditions: Liquids having a flash point below 22.8°C (73°F) and having a boiling point at or above 37.8°C (100°F) and those liquids having a flash point at or above 22.8°C (73°F) and below 37.8°C (73°F) and below 37.8°C (100°F) (i.e. Class IB and IC liquids). Materials that, on account of their physical form or environmental conditions, can form explosive mixtures with air and are readily dispersed in air. Flammable or combustible dusts with a representative diameter less than 420 microns (40 mesh). Materials that burn with extreme rapidity, usually by reason of self-contained oxygen (e.g. dry nitrocellulose and many organic peroxides). Solids containing greater than 0.5 percent by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. **4** Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and will burn readily: Flammable gases. Flammable cryogenic materials. Any liquid or gaseous materials that is liquid while under pressure and has a flash point below 22.8°C (73°F) and a boiling point below 37.8°C (100°F) (i.e. Class IA liquids). Materials that ignite when exposed to air. Solids containing greater than 0.5 percent by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent.

INSTABILITY HAZARD: 0 Materials that in themselves are normally stable, even under fire conditions: Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) below 0.01 W/mL. Materials that do not exhibit an exotherm at temperatures less than or equal to 500°C (932°F) when tested by differential scanning calorimetry. **1** Materials that in themselves are normally stable, but that can become unstable at elevated temperatures and pressures: Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 0.01 W/mL and below 10 W/mL. **2** Materials that readily undergo violent chemical change at elevated temperatures and pressures: Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 10 W/mL and below 100 W/mL. **3** Materials that in themselves are capable of detonation or explosive decomposition or explosive reaction, but that require a strong initiating source or that must be heated under confinement before initiation: Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 100 W/mL and below 1000 W/mL. Materials that are sensitive to thermal or mechanical shock at elevated temperatures and pressures. **4** Materials that in themselves are readily capable of detonation or explosive decomposition or explosive reaction at normal temperatures and pressures: Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) of 1000 W/mL or greater. Materials that are sensitive to localized thermal or mechanical shock at normal temperatures and pressures.

DEFINITIONS OF TERMS (Continued)

FLAMMABILITY LIMITS IN AIR:

Much of the information related to fire and explosion is derived from the **National Fire Protection Association (NFPA)**. **Flash Point** - Minimum temperature at which a liquid gives off sufficient vapors to form an ignitable mixture with air. **Autoignition Temperature**: The minimum temperature required to initiate combustion in air with no other source of ignition. **LEL** - the lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source. **UEL** - the highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source.

TOXICOLOGICAL INFORMATION:

Human and Animal Toxicology: Possible health hazards as derived from human data, animal studies, or from the results of studies with similar compounds are presented. Definitions of some terms used in this section are: **LD₅₀** - Lethal Dose (solids & liquids) which kills 50% of the exposed animals; **LC₅₀** - Lethal Concentration (gases) which kills 50% of the exposed animals; **ppm** concentration expressed in parts of material per million parts of air or water; **mg/m³** concentration expressed in weight of substance per volume of air; **mg/kg** quantity of material, by weight, administered to a test subject, based on their body weight in kg. Other measures of toxicity include **TDLo**, the lowest dose to cause a symptom and **TCLo** the lowest concentration to cause a symptom; **TDo**, **LDLo**, and **LDo**, or **TC**, **TCo**, **LCLo**, and **LCo**, the lowest dose (or concentration) to cause lethal or toxic effects. **Cancer Information**: The sources are: **IARC** - the International Agency for Research on Cancer; **NTP** - the National Toxicology Program, **RTECS** - the Registry of Toxic Effects of Chemical Substances, **OSHA** and **CAL/OSHA**. IARC and NTP rate chemicals on a scale of decreasing potential to cause human cancer with rankings from 1 to 4. Subrankings (2A, 2B, etc.) are also used. **Other Information**: **BEI** - ACGIH Biological Exposure Indices, represent the levels of determinants which are most likely to be observed in specimens collected from a healthy worker who has been exposed to chemicals to the same extent as a worker with inhalation exposure to the TLV.

ECOLOGICAL INFORMATION:

EC is the effect concentration in water. **BCF** = Bioconcentration Factor, which is used to determine if a substance will concentrate in lifeforms which consume contaminated plant or animal matter. **TL_m** = median threshold limit; Coefficient of Oil/Water Distribution is represented by **log K_{ow}** or **log K_{oc}** and is used to assess a substance's behavior in the environment.

REGULATORY INFORMATION:

U.S. and CANADA:

ACGIH: American Conference of Governmental Industrial Hygienists, a professional association which establishes exposure limits.

This section explains the impact of various laws and regulations on the material. **EPA** is the U.S. Environmental Protection Agency. **NIOSH** is the National Institute of Occupational Safety and Health, which is the research arm of the U.S. Occupational Safety and Health Administration (**OSHA**). **WHMIS** is the Canadian Workplace Hazardous Materials Information System. **DOT** and **TC** are the U.S. Department of Transportation and the Transport Canada, respectively. Superfund Amendments and Reauthorization Act (**SARA**); the Canadian Domestic/Non-Domestic Substances List (**DSL/NDSL**); the U.S. Toxic Substance Control Act (**TSCA**); Marine Pollutant status according to the **DOT**; the Comprehensive Environmental Response, Compensation, and Liability Act (**CERCLA or Superfund**); and various state regulations. This section also includes information on the precautionary warnings which appear on the material's package label. **OSHA** - U.S. Occupational Safety and Health Administration.

EUROPEAN and INTERNATIONAL:

The DFG: This is the Federal Republic of Germany's Occupation Health Agency, similar to the U.S. OSHA. **EU** is the European Union (formerly known as the **EEC**, European Economic Community). **EINECS**: This is the European Inventory of Now-Existing Chemical Substances. The **ARD** is the European Agreement Concerning the International Carriage of Dangerous Goods by Road and the **RID** are the International Regulations Concerning the Carriage of Dangerous Goods by Rail. **AICS** is the Australian Inventory of Chemical Substances. **METI** is the Japanese Ministry of Economy, Trade, and Industry.